



MOSA GE SX-12054 KDT STAGEV

Product price:

7,415.00 € tax excluded

Product description:

MOSA GE SX-12054 KDT 8.8 KW

MOSA GE SX-12054 KDT three-phase generator set of 8.8 KW with KOHLER KDW702 diesel engine. The MOSA GE SX-12054 KDT generator set is equipped with electric starter. The alternator of the MOSA GE SX-12054 KDT generator set is synchronous, three-phase, self-excited, self-regulated with class H insulation.

This MOSA GE SX-12054 KDT generator set is compact and easy to handle and transport thanks to its compact size, its weight of 350 kg as well as the practical central hook for lifting. Generator with canopy to reduce noise emissions which makes it super silent.

The MOSA GE SX-12054 KDT generator with 38 litre tank has a fuel consumption of 2.6 litres/hour at 75% load for an autonomy of more than 14 hours.

Sockets:

1x 400V 16A 3P+N+T CEE 2x 230V 16A 2P+T Schuko

Technical specifications:

Maximum power three-phase: 8.8 KW Continuous use power three-phase: 8 KW Maximum power three-phase: 11 KVA

Continuous use power three-phase: 10 KVA Single-phase continuous use power: 7 KW Single-phase continuous use power: 7 KVA

Fuel: Diesel

Voltage: 230 V / 400 V Frequency: 50 Hz

Engine: KOHLER KDW702

Starting: Electric

Consumption: 2.6 Lt/h at 75% load

Length: 1568 mm



Width: 710 mm Height: 1115 mm Weight: 350 Kg Supersilenced

MOSA generator set GE SX-12054 KDT portable - KOHLER KDW702 diesel engine electric start - Three-phase alternator

If you are looking for another product such as the MOSA GE SX-12054 KDT generator set then you can consult our catalogue for other <u>terrestrial generator sets</u>.

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Single phase / Three phase Continuous power single phase (KW): 7 Continuous power single phase (KVA): 7 Maximum power three phase (KW): 8.8 Continuous power three phase (KW): 8 Maximum power three phase (KVA): 11 Continuous power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE IP67 - 2 x 230V 16A 2P+T Schuko IP68

Engine: KOHLER KDW702 Emissions Regulations: Stage 5

Engine rpm (rpm): 3000
Speed governor: Mechanical

Starting system: Elettrico Engine capacity (cm³): 686

Number cylinders: 2 Oil capacity (L): 1.6 Cooling: Water

Alternator: Synchronous self-excited, self-regulated

Bore x stroke (mm): 75 x 77.6 Fuel tank capacity (L): 38



Consumption (L/h): 2.6 Running time (h): 14.5 Acoustic power: 93 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 1568 Width (mm): 710 Height (mm): 1115 Dry weight (Kg): 350

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Kubota

