



HONDA Outboard BF 200D XDU

Product price:

16,520.00 € tax excluded

Product description:

HONDA OUTBOARD BF200D XDU EXTRALONG SHAFT

Honda BF200D XDU DBW outboard engines are perfect for professional use, they are reliable, compact and lightweight complete with PGM-IG electronic injection system.

Honda BF200D XDU DBW are optimized to offer more power for a wide range of different boats. The decisive, smooth power this advanced technology offers is sure to put a smile on your face as you venture out on the water.

VTEC™ is an efficient system included in the Honda BF200D XDU outboard that keeps fuel consumption down while delivering an exciting increase in power. In the Honda BF200D XDU it works by using two different cams:

- 1) When the engine is running at low rpm, the valves are operated by a cam less aggressively ensuring low fuel consumption and excellent performance.
- 2) As the engine speed increases to 5000 rpm, the VTEC[™] system hydraulically operates a cam with a higher lift profile. This keeps the valves open longer, getting more air into the combustion chamber to produce optimum power, just like in a Formula One race car.

Honda BF200D XDU are large displacement engines, featuring high torque value at all operating speeds, give high acceleration and exceptional top speeds. Honda's exclusive BLAST, PGM-FI, VTEC (for BF225 and BF250) and ECOmo technologies together with the performance of the footmounted gearbox ensure smooth power delivery with minimal hydrodynamic resistance.

HONDA BF200D XDU TECHNICAL FEATURES

Net Power (Hp): 200 Displacement: 3583 cm³ Shaft Length: Extra Long Dry Weight (Kg): 287



Start: Electric

Initiation System: Electronic PGM-IG

Type of Control: Remote Engine trim and lift: Electric Transom height (mm): 635

Length (mm): 920 Width (mm): 660 Height (mm): 1915

Bore x stroke: 89 x 96 mm Brand Engine: Honda Engine Type: OHC V6

Number of cylinders: 6

RPM at full throttle (rpm): 5000-6000

Cooling system: Water

Battery charging capacity (A): 60 Exhaust system: Propeller hub Propeller rotation: Normal

Are you looking for an outboard with different technical specifications? <u>Here</u> you can find the full range of Honda or other specialized brands.

The images are purely indicative.

Product features:

Fuel: Gasoline Engine: OHC V6

Ignition: Electronic PGM-IG Starting system: Electric Engine capacity (cm³): 3583

Number cylinders: 6

Cylinders' position: V to 90° Cooling: Water (with thermostat) Bore x stroke (mm): 89 x 96

Rpm at full throttle (rpm): 5000 - 6000 Appearance and engine lifting: Electric

Transom height (mm): 635

Length (mm): 920



Width (mm): 660 Height (mm): 1915 Dry weight (Kg): 287 Shaft Length: X

Controls: Remote

