



MASE IS 19 K MARINE GENERATOR SINGLE- PHASE 20KW EPA

Product price:

19,950.00 € tax excluded

Product description:

MASE IS 19 K SINGLE PHASE MARINE GENERATOR 20KW

MASE IS19K single-phase marine generator with KUBOTA V2203 engine with diesel power supply at 1800 rpm capable of delivering a power of 20KW.

The MASE IS19K is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS19K marine generator is built with Kubota diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS19K.

The soundproof cabin of the MASE IS19K consists of a load-bearing structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely light and very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the genset installed in narrow spaces.

The MASE IS19K marine generator has **EPA certification** valid only for the **American market**.

Technical Features:

Phase Type: Single Phase

Maximum Power: 20KW

Fuel: Diesel

Voltage: 120 / 240 V

Frequency: 60 Hz

Motor: KUBOTA V2203, 4 Stroke



Length: 1115 mm

Width: 585 mm

Height: 730 mm

Weight: 475 Kg

If you are looking for another generator as the MASE IS19K then you can see the entire catalog of [marine generator sets](#).

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 20

Fuel: Diesel

Frequency (Hz): 60

Voltage (V): 120 / 240

Engine: KUBOTA V2203

Engine rpm (rpm): 1800

Speed governor: Electronic

Engine capacity (cm³): 2197

Number cylinders: 4

Cooling: Air / water (Intercooler W/A)

Inyección : Indirect

Alternator: Synchronous, self-excited

Poles: 4

Lubrication: Forced

Consumption (L/h): 6.5

Acoustic pressure: 49 dB(A) at 7 m

Length (mm): 1115

Width (mm): 585

Height (mm): 730

Dry weight (Kg): 475

Inverter: No

AVR: Yes

Compound: No



Shop name

Silenced: Yes

Super silenced: Yes



PrestaShop