



# MASE IS 28.06 K MARINE GENERATOR SINGLE-PHASE 30KW EPA

## Product description:

### **MASE IS 28.06 K SINGLE PHASE MARINE GENERATOR 30KW**

MASE IS28,06K single-phase marine generator with KUBOTA V3300 engine with diesel power supply at 1800 rpm capable of delivering a power of 30KW.

The MASE IS28,06K marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS28,06K is built with Kubota diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS28,06K.

The soundproof cabin of the MASE IS28,06K is made up of a bearing structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely light and of very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the genset installed in narrow spaces.

The MASE IS28.06K marine generator has **EPA certification** valid only for the **American market**.

## Technical Features:

Phase Type: Single Phase

Maximum Power: 30KW

Fuel: Diesel

Voltage: 120 / 240 V

Frequency: 60 Hz



Motor: KUBOTA V3300, 4 Stroke  
Length: 1260 mm  
Width: 640 mm  
Height: 830 mm  
Weight: 630 Kg

If you are looking for another generator as the MASE IS28,06K then you can see the entire catalog of [marine generator sets](#).

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 30  
Fuel: Diesel  
Frequency (Hz): 60  
Voltage (V): 120 / 240  
Engine: KUBOTA V3300-BG  
Engine rpm (rpm): 1800  
Speed governor: Electronic  
Engine capacity (cm<sup>3</sup>): 3318  
Number cylinders: 4  
Cooling: Air / water (Intercooler W/A)  
Inyección : Indirect  
Alternator: Synchronous, self-excited  
Poles: 4  
Lubrication: Forced  
Consumption (L/h): 13 at 100% of the load  
Acoustic pressure: 54 dB(A) at 7 m  
Length (mm): 1260  
Width (mm): 640  
Height (mm): 830  
Dry weight (Kg): 630  
Inverter: No  
AVR: Yes



Compound: No

Silenced: Yes

Super silenced: Yes

