

MASE IS 16.8 T MARINE GENERATOR THREE-PHASE 16.8KVA

Product description:

Ø.

MASE IS 16.8 T THREE-PHASE MARINE GENERATOR 16.8KVA

MASE IS16,8T three-phase marine generator with Yanmar 3TNV88 engine with diesel power supply at 1800 rpm capable of delivering a power of 16.8KVA.

The MASE IS16,8T marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS16,8T marine generator is built with a diesel-powered Yanmar engine and synchronous, self-excited alternator with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS16.8T.

The soundproof cabin of the MASE IS16,8T is made of an aluminum profile structure that supports panels in marine aluminum painted type 5754 extremely light and very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the genset installed in narrow spaces.

Technical Features:

Phase Type: Three Phase Maximum Power: 16.8KVA Fuel: Diesel Voltage: 240 - 480 V Frequency: 60 Hz Motor: Yanmar 3TNV88, 4 Stroke Length: 985 mm

PrestaShop

(R)

Width: 585 mm Height: 730 mm Weight: 344 Kg

Ø.

If you are looking for another generator like the MASE IS16,8T then you can see the entire catalog of marine generator sets.

Images and technical data are not binding.

Product features:

Phase: Three phase Maximum power three phase (KVA): 16.8 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 240 - 480 V Engine: Yanmar 3TNV88, 4 stroke Engine rpm (rpm): 1800 Speed governor: Centrifugal, mechanical Engine capacity (cm³): 1642 Number cylinders: 3 Oil capacity (L): 5.5 Cooling: Air / water (Intercooler W/A) Inyección : Direct Alternator: Synchronous, self-excited Poles: 4 Lubrication: Forced Consumption (L/h): 4 at 100% of the load Acoustic pressure: 51 dB(A) at 7 m Length (mm): 985 Width (mm): 585 Height (mm): 730 Dry weight (Kg): 344 Inverter: No AVR: Yes Compound: No Silenced: Yes Super silenced: Yes Product type: Generator Voltage regulator: AVR Engine manufacturer: Yanmar