



AIRSTAR SIROCCO 1000 REDTECH 99000 lm

Product description:

AIRSTAR SIROCCO1000 REDTECH 99000 lm

AIRSTAR SIROCCO1000 REDTECH is a lightglobe equipped with 18 LED lamps capable of delivering a total light output of 700W, thanks to which it can illuminate an area of 4071m².

The AIRSTAR SIROCCO1000 REDTECH 99000 lumen lightglobe is a perfect device for night work and on-site interventions, such as temporary site lighting, industrial maintenance or emergency.

AIRSTAR SIROCCO1000 REDTECH features a multi-lamp system that allows the balloon, in the event of a lamp failure, to continue to operate.

AIRSTAR SIROCCO1000 REDTECH comes complete with full lightglobe, 1 carrying bag, 1 user manual, 1 envelope repair kit. **Stand and sand bags optional.**

The Airstar RedTech line of lightglobe is equipped with wifi and bluetooth connection, can be controlled via dedicated app, downloadable on both IOS and android, giving you the ability to make several adjustments including light intensity, blinking light and many other adjustments.

CARACTERISTICS TECHNICAL AIRSTAR SIROCCO1000 REDTECH:

Light Engine: Airstar LED Matrix: 18 x 5500 lm

Luminous flux: 99000 Lm

Average LED life: 50000 H



Color temperature: Daylight 5000 K

CRI: 70

Lighting under the balloon (placed at 4 meters): 660 Lx

Lighting area for activities at the first level of risk (standard EN12464-2): 907 m²

Lighting area open space environment (standard EN1838): 4071 m²

Wind resistance of the balloon: 100 km/h - 60 mph

Power consumption: 700 W

Efficiency: 141 lm/W - 11511 lm/kg - 5221 lm/lb

Power supply voltage: 100~240 VAC / 50-60 Hz

Recommended battery: 1,5 kWh

Overall protection class: IEC-60598-1, CE, IP54

Type of lamps: LED

Transport bag: 108 x 30 x 30 cm (L*w*h) 42 x 11 x 11 in (L*w*h)

Weigh: 15.5 Kg

Looking for a Lightglobe with different technical features? [Here](#) you can find the full range of Lightglobe AIRSTAR or other specialized brands.

Images and technical data not binding.

Product features:

Frequency (Hz): 50 / 60

Voltage (V): 100 - 240

Protection degree: IEC-60598-1, CE, IP54

Power (W): 700

Average life of LEDs (hrs): 50000

Colour temperature (°K): 5000

Type of lamps: LED

Lamps: 18

Telescopic pole: Acciaio cromato

Illuminated area (m²): 4071

Total lumens (Lm): 99000

Weight (Kg): 0.4

Video: wNqAxWPD5n4

