



GREEN POWER GP77 TR/S SINGLE-PHASE / THREE-PHASE PTO GENERATOR 75KVA

Product price:

3.972,00 € tax excluded

Product description:

GREEN POWER GP77 TR/S SINGLE-PHASE / THREE-PHASE PTO GENERATOR 75KVA

Generator GREEN POWER GP77 TR/S Three-phase PTO, equipped with MECC ALTE ECP32-3L/4 alternator capable of delivering a power of 75KVA, complete with **AVR voltage regulator**.

The GREEN POWER GP77 TR/S generator is very reliable as it has been built and designed using top quality materials. The generator is easy to transport, install and position due to its compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 150 HP and a PTO speed of at least 420 rpm. The minimum parameters indicated are necessary for the correct functioning of the PTO generator, if they are not respected it is possible to cause malfunctions of the equipment.

The GREEN POWER GP66 TR/S generator is equipped with an electric panel complete with:

- Thermomagnetic circuit breaker
- Differential
- Socket 63 A 400 V
- Socket 16 A 230 V
- E31 digital module complete with: Voltmeter, Frequency meter and Hour meter

TECHNICAL FEATURES PTO GENERATOR GREEN POWER GP77 TR/S

Phase type: Single-phase / Three-phase

Maximum three-phase power: 78 KVA / 62.4 KW



Continuous three-phase power: 75 KVA / 60 KW
Voltage: 230 - 400 V
Frequency: 50 Hz
Engine rpm: 1500 rpm
Necessary tractor power: 150 hp
PTO speed: 420 rpm
Alternator: MECC ALTE ECP32- 3L / 4 (OR QUIVALENT)
N ° of poles: 4
Insulation class: H
Protection class: IP 23
Voltage regulator: AVR
Length : 1140 mm
Width: 750 mm
Height: 1065 mm
Weight: 454 Kg

Are you looking for a PTO generator with different technical characteristics? Here you can find the full range of Green Power or other brands specializing in the field

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 78
Continuous power three phase (KW): 60
Maximum power three phase (KVA): 62.4
Continuous power three phase (KVA): 75
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine rpm (rpm): 1500
Alternator: MECC ALTE ECP32-3L/4
Poles: 4
Protection degree: IP23
PTO speed (round/min): 420
Required tractor power: 150 Hp
Length (mm): 1140
Width (mm): 750
Height (mm): 1065
Dry weight (Kg): 454
Silenced: No
Super silenced: No
Voltage regulator: AVR

