

MASE MARINER 1304 S SINGLE PHASE MARINE GENERATOR SILENCED 12KW

Product description:

Ø.

MASE MARINER 1304 S SILENCED SINGLE-PHASE MARINE GENERATOR 12KW

MASE MARINER1304S single-phase silenced marine generator is equipped with a YANMAR 3TNV88 diesel engine capable of delivering a maximum power of 12 KW at 1800 rpm.

The MASE MARINER1304S is built with and synchronous alternator, self-excited with air cooling, is extremely compact and powerful, suitable even on small boats. The alternator is complete with a voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like that of the house.

The MASE MARINER1304S allows easy access for maintenance of the power and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER1304S is equipped with a soundproof cabin that makes it super silent, with a sound emission of 54dB(A) at a distance of 7 m. The painted aluminum soundproof cabin is extremely lightweight and of very high resistance to external agents.

TECHNICAL FEATURES MASE MARINER1304S

Phase Type: Single Phase Maximum Power: 12 KW Fuel: Diesel Voltage: 120 - 240 V Frequency: 60 Hz Motor: YANMAR 3TNV88, 4 Stroke Mechanical Power: 20. 4 Hp Number of Cylinders: 3

PrestaShop

(121)

Displacement: 1642 cc Engine RPM: 1800 rpm Fuel Consumption: 4 l/h Sound Pressure: 54 dB(A) @ 7 m Alternator: Synchronous Brushless Voltage Regulator: Yes Length: 1040 mm Width: 631 mm Height: 694 mm Weight: 344 Kg

If you are looking for another marine generator then you can browse the entire catalog of marine generators.

Images and technical data are not binding.

Product features:

Ø.

Phase: Single phase Maximum power single phase (KW): 12 Fuel: Diesel Frequency (Hz): 60 Voltage (V): 120 / 240 Engine: YANMAR 3TNV88 Engine rpm (rpm): 1800 Speed governor: Centrifugal, mechanical Engine capacity (cm³): 1642 Number cylinders: 3 Cooling: Air Inyección : Direct Alternator: Synchronous, self-excited Poles: 4 Lubrication: Forced Consumption (L/h): 4 at 100% of the load Acoustic pressure: 53 dB(A) at 7 m Length (mm): 1040 Width (mm): 631 Height (mm): 694 Dry weight (Kg): 344 Inverter: No AVR: No Compound: No Silenced: Yes

Super silenced: Yes Voltage regulator: YES