

## MASE MARINER 2460 KS SINGLE PHASE MARINE GENERATOR SILENCED 24KW EPA

## **Product description:**

MASE MARINER 2460 KS SILENCED SINGLE-PHASE MARINE GENERATOR 24 KW EPA

MASE MARINER2460KS single-phase silenced marine generator is equipped with a KUBOTA V2403 Diesel engine with **EPA emissions standard**, capable of delivering a maximum power of 24 KW at 1800 rpm.

The MASE MARINER2460KS alternator is a 4-pole synchronous, self-regulated, self-excited, brushless alternator, which in combination with the powerful KUBOTA engine can deliver a maximum power of 24 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the one at home.

The MASE MARINER2460KS allows easy access for maintenance of the alimentation and lubrication systems, seawater pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER2460KS is equipped with a soundproof cabin that makes it super silent, with a sound emission of 51dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER2460KS marine generator has **EPA certification** valid only **for the US market**.

TECHNICAL FEATURES MASE MARINER2460KS

Phase Type: Single Phase Maximum Power: 24 KW Fuel: Diesel Voltage: 120 - 240 V

PrestaShop

Frequency: 60 Hz Engine: KUBOTA V2403, 4 Stroke Emissions Standard: EPA Mechanical Power: 39. 8 Hp Number of cylinders: 4 Displacement: 2434 cc Engine RPM: 1800 rpm Fuel consumption: 6.5 l/h Sound pressure: 51 dB(A) @ 7 m Alternator: Synchronous Brushless Voltage regulator: AVR Length: 1135 mm Width: 631 mm Height: 694 mm Weight: 465 Kg

Ø.

If you are looking for another marine generator then you can browse the entire catalog of marine generators.

Images and technical data are not binding.

## **Product features:**

Phase: Single phase Maximum power single phase (KW): 24 Fuel: Diesel Frequency (Hz): 60 Voltage (V): 120 / 240 Engine: KUBOTA V2403 **Emissions Regulations: EPA** Engine rpm (rpm): 1800 Speed governor: Electronic Engine capacity (cm<sup>3</sup>): 2434 Number cylinders: 4 Cooling: Air Invección : Indirect Alternator: Synchronous, self-excited Poles: 4 Lubrication: Forced Consumption (L/h): 6.5 Acoustic pressure: 51 dB(A) at 7 m Length (mm): 1135 Width (mm): 631

R

Height (mm): 694 Dry weight (Kg): 465 Inverter: No AVR: Yes Compound: No Silenced: Yes Super silenced: Yes Voltage regulator: AVR

