



TELWIN MASTERCHARGE 740 ELECTRIC CAR CHARGING STATION 7,4KW

Product price:

740.00 € tax excluded

Product description:

TELWIN MASTERCHARGE 740 ELECTRIC CAR CHARGING STATION 7,4KW

TELWIN MASTERCHARGE 740 is a charging station for electric cars capable of delivering a maximum power of 7,4 KW with digital interface.

With the TELWIN electric car charging station, you can reap the benefits of electromobility in an efficient and optimized way to meet your needs both for your business and at home.

TELWIN MASTERCHARGE 740 is complete with an RFID badge, so you can set up your station to deliver power only when your personal badge is passed.

The TELWIN MASTERCHARGE 740 Electric Car Station boasts high charging output, maximum safety and maximum convenience. Charging with the TELWIN electric car station is faster than a typical household outlet and automatically shuts off as soon as the battery is full.

Dynamic load management from TELWIN not only saves you money, but also helps avoid load spikes and therefore power outages. This is because it manages the accurate phase control of the power load within a system. The total available power is matched to the building's energy consumption and the charging capacity is intelligently distributed to the connected electric cars.

TELWIN MASTERCHARGE 740 TECHNICAL FEATURES:

Maximum Current: 32A Phase Type: Single Phase

Main Voltage: 230 V Main Frequency: 50 Hz

Overvoltage Category: III according to EN 60664



Protection Class: IP54 Cable Length: 5. 0 m Cable type: Class C

Mechanical impact protection: IK08

Output voltage: 230 V

Maximum charging power: 7,4 KW

Width: 325 mm Depth: 215 mm Height: 77 mm Weight: 4,5 Kg

If you are looking for a TELWIN charging station or similar products then you can browse our entire <u>catalogue</u>.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 7.4

Frequency (Hz): 50 Voltage (V): 230

Protection degree: IP54 Nominal current (A): 32

Length (mm): 325 Width (mm): 215 Height (mm): 77

Product type: Charging station

Weight (Kg): 4,5

Overvoltage category: III in accordance with EN 60664

Assembly: Wall or stand mounting

Power cable: Mounted on-wall or in-wall

Charging cable: Case C Output voltage (VAC): 230

