



# ITALTOWER PC750 PRO03 LIGHTING TOWER 4x320 W MULTILED WITH SLOW TROLLEY AND GENERATOR

## Product description:

### ITALTOWER PC750 PRO03 LIGHTING TOWER 4x320 W MULTILED WITH SLOW TROLLEY AND GENERATOR

The ITALTOWER PC750 PRO03 Light Tower is equipped with a Kohler 15KD350 Diesel engine, capable of delivering a power of 7KW at the service of 4 LED lamps 320W.

Thanks to the 4 LED projectors ITALTOWER PC750 PRO03 can illuminate an area of 4500 square meters with a maximum luminous intensity of 166200 lm. The winch allows the manual lifting of the telescopic pole in safety thanks to an iron cable composed of 133 micro anti-twist cables improving the resistance and the capacity of the winch itself.

The ITALTOWER PC750 PRO03 is equipped with a Kohler 15KD350 Stage V engine, fully compliant with the latest European emission regulations. One of the strong points of the ITALTOWER PC750 PRO03 is undoubtedly its retractable tiller, which can be locked in a vertical position, thus facilitating the transport or storage of the tower.

ITALTOWER PC750 PRO03 has been designed in particular to simplify the operations of the Civil Protection. Practical model to install and fast to transport is indicated for applications where it is required an immediate intervention as the first aid or to illuminate an escape route.

## TECHNICAL FEATURES ITALTOWER PC750 PRO03

Number of lights: 4

Lamps power: 320 W LED

Lumen: 166200 lm

Illuminated area: 4500 sqm



Phase type: Single phase  
Maximum power: 7 KW  
Sound pressure: 70dB(A) @ 7m  
Voltage: 230 V  
Frequency: 50 - 60 Hz  
Auxiliary Power: 3 kVA  
Motor: Kohler 15KD350  
RPM: 3000rpm  
Coolant: Air  
Emissions Standard: Stage V  
Alternator: Linz Alumen  
Tank capacity: 45 l  
Fuel: Diesel  
Range: 84 h  
Maximum height: 7.5m  
Lifting system: Manual  
Rotation: 355°  
Wind resistance: 110 Km/h  
Trolley: Slow pull trolley  
Stabilizers 4 + 1 (wheels)  
Length (mm): min 1550 - Max 2400  
Width (mm): min 1200 - Max 2400  
Height (mm): min 2400 - Max 7500  
Dry weight (Kg): 620

Are you looking for a light tower with different characteristics? [Here](#) you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 7  
Fuel: Diesel  
Frequency (Hz): 50 / 60  
Voltage (V): 230  
Engine: Kohler 15KD350  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Number cylinders: 1



Cooling: Air  
Alternator: Linz  
Type of lamps: MULTILED  
Lamps: 4 x 320 W  
Telescopic pole: Vertical  
Illuminated area (m<sup>2</sup>): 4500  
Total lumens (Lm): 166200  
Lifting System: Manual lifting system  
Maximum height (m): 7.5  
Mast rotation: 355°  
Open size (mm): 2400 x 2400 x 7500  
Length closed (mm): 1550  
Width closed (mm): 1200  
Height closed (mm): 2400  
With generator / Without generator: With generator  
Transportability: Slow Trailer  
Stability to wind (Km/h): 110  
Fuel tank capacity (L): 45  
Running time (h): 84  
Acoustic pressure: 70 dB(A) at 7 m  
Engine manufacturer: Kohler  
Weight (Kg): 620

