



ITALTOWER PEGASO PRO02 LIGHTING TOWER 4x75 W MULTILED WITH HAND CART AND GENERATOR

Product price:

3,464.00 € tax excluded

Product description:

ITALTOWER PEGASO PRO01 LIGHTER TOWER 4x75 W MULTILED WITH HAND CART AND GENERATOR

ITALTOWER PEGASO PRO02 Light Tower is equipped with an Arion 6000 engine powered by gasoline, capable of delivering a power of 4.8KW at the service of 4 LED lamps of 75W.

The ITALTOWER PEGASO PRO02 is a compact and easy to use, with its handy trolley you can move it anywhere. Ideal for bringing light in remote areas or open countryside where there is poor lighting.

Thanks to 4 LED projectors ITALTOWER PEGASO PRO02 can illuminate an area of 1500 square meters with a maximum luminous intensity of 36900 lm. ITALTOWER PEGASO PRO02 is supplied with two retractable handles for easy transport even on uneven ground and with 3 stabilizers (2 front and 1 rear) for optimal stabilization.

TECHNICAL FEATURES ITALTOWER PEGASO PRO02

Number of lights: 4

Lamps power: 75 W LED

Lumen: 36900 lm

Lit area: 1500 square meters Phase type: Single-phase Maximum power: 4.8 KW

Sound pressure: 70dB(A) @ 7m

Voltage: 230 V



Frequency: 50 Hz

Auxiliary power supply: 3.2 kVA

Motor: Arion 6000 RPM: 3000rpm Coolant: Air

Emission regulations: Not Emitted

Alternator: Arion 6000 Tank Capacity: 25 I Fuel: Gasoline Autonomy: 27 h

Fuel Consumption: 0.9 I/h Maximum Height: 5.5m Lifting System: Manual

Rotation: 350°

Wind Resistance: 80 Km/h

Trolley: Hand Towing

Outriggers: 2

Length (mm): min 1300 - Max 1300 Width (mm): min 560 - Max 800 Height (mm): min 2380 - Max 5500

Dry Weight (Kg): 250

Are you looking for a light tower with different characteristics? <u>Here</u> you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Phase: Single phase

Maximum power single phase (KW): 4.8

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 Engine: Arion 6000

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000 Number cylinders: 1

Cooling: Air

Alternator: Arion 6000 Type of lamps: MULTILED



Lamps: 4 x 75 W

Telescopic pole: Vertical Illuminated area (m²): 1500 Total lumens (Lm): 36900

Lifting System: Manual lifting system

Maximum height (m): 5.5

Mast rotation: 350°

Open size (mm): 1300 x 800 x 5500

Lenght closed (mm): 1300 Width closed (mm): 560 Height closed (mm): 2380

With generator / Without generator: With generator

Transportability: Wheels and handles Stability to wind (Km/h): 80 Km/h

Fuel tank capacity (L): 25 Consumption (L/h): 0.9

Acoustic pressure: 70 dB(A) at 7 m

Voltage regulator: AVR

Weight (Kg): 250