



ITALTOWER TOWERLOOP PRO02 LIGHT TOWER 4x75W MULTILED

Product price:

3,740.00 € tax excluded

Product description:

ITALTOWER TOWERLOOP PRO02 LIGHT TOWER 4x75W MULTILED

ITALTOWER TOWERLOOP PRO02 is a light tower equipped with 4 led projectors 75W high brightness with directional optics and handles for easy rotation, with a lifting system that allows an extension up to 7 mt.

The ITALTOWER TOWERLOOP PRO02 light tower is supplied with a plug socket kit for the connection in series of several units up to a maximum of 6. The ITALTOWER TOWERLOOP PRO02 is supplied with galvanized guides and eyebolts for moving and lifting. These features make the operation by the operator very simple, making the unit easy to handle and use.

The efficient manual lifting system is able to bring the projectors to a height of 7 m, combined with 4 LED lamps, the light tower can illuminate an area of 2000 square meters with a maximum luminous intensity of 36900 lm.

The ITALTOWER TOWERLOOP PRO02 is equipped with 4 stabilizers which make the light tower resistant to strong wind gusts up to 100 km/h. ITALTOWER TOWERLOOP PRO02 is NOT equipped with an internal generator, but in return it can be effectively powered by an external source such as a generator set or can be connected directly to the power grid.

ITALTOWER TOWERLOOP PRO02 TECHNICAL FEATURES

Number of luminaires: 4



Lamp wattage: 75 W multiLED

Lumen: 36900 lm

Illuminated area: 2000 square metres

Phase type: Single phase

Voltage: 110 / 230 V

Frequency: 50 Hz (60 Hz ONLY ON REQUEST

Output: 230 V 16A Maximum height: 7 m Lifting system: Manual

Rotation: 359°

Wind resistance: 100 Km/h Trolley: Hand-drawn trolley

Stabilisers: 4

Length (mm): min 930 - MAX 1800 Width (mm): min 800 - MAX 1600 Height (mm): min 2300 - Max 7000

Dry weight (Kg): 235

Are you looking for a light tower with different characteristics? <u>Here</u> you can find the full range of light towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Phase: Single phase Frequency (Hz): 50 Voltage (V): 110 / 230 Type of lamps: MULTILED

Lamps: 4 x 75 W

Telescopic pole: Vertical Illuminated area (m²): 2000

Lifting System: Manual lifting system

Maximum height (m): 7 Mast rotation: 359° Open size (mm):

Lenght closed (mm): 930 Width closed (mm): 800 Height closed (mm): 2300

With generator / Without generator: Without generator

Transportability: Stationary



Stability to wind (Km/h): 100 Km/h Weight (Kg): 235

