



ITALTOWER BARROW PRO02 LIGHTING TOWER 4x160 W MULTILED WITH HAND CART

Product price:

3,073.00 € tax excluded

Product description:

ITALTOWER BARROW PRO02 LIGHTHOUSE TOWER 4x160 W MULTILED WITH HAND CARRIAGE

ITALTOWER BARROW PRO02 is a light tower equipped with 4 high brightness 160W LED projectors complete with hand truck, with a manual lifting system that allows an extension up to 5.5 meters.

The ITALTOWER BARROW PRO02 is a compact and easy to use light tower, with its practical trolley you can move it anywhere. Ideal for bringing light in remote areas or open countryside where there is poor lighting.

With 4 LED projectors ITALTOWER BARROW PRO02 light tower can illuminate an area of 2400 square meters with a maximum luminous intensity of 81400 lm. ITALTOWER BARROW PRO02 is supplied with two retractable handles for easy transport even on uneven ground and with 3 stabilizers (2 front and 1 rear) for optimal stabilization.

The manual winch allows the lifting of the telescopic pole in safety thanks to an iron cable composed of 133 anti-twisting micro cables improving the resistance and the capacity of the winch itself. ITALTOWER BARROW PRO02 light tower is suitable for applications where it is required the use of small professional generators, up to 6KVA, with maximum dimensions 900 x 600 mm.

ITALTOWER BARROW PRO02 TECHNICAL FEATURES

Number of lights: 4

Lamps power: 160 W multiLED

Lumen: 81400 lm



Illuminated area: 2400 sqm Phase type: Single phase

Voltage: 230 V Frequency: 50 Hz Maximum height: 5,5 m Lifting system: Manual

Rotation: 350°

Wind resistance: 80 Km/h Trolley: Trolley with hand tow

Generator support base: 900 x 600 mm

Stabilizers: 2

Length (mm): min 1200 Width (mm): min 840

Height (mm): min 2200 - Max 5500

Dry weight (Kg): 192

Are you looking for a light tower with different characteristics? <u>Here</u> you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Phase: Single phase Frequency (Hz): 50 Voltage (V): 230

Type of lamps: MULTILED

Lamps: 4 x 160 W

Telescopic pole: Vertical Illuminated area (m²): 2400 Total lumens (Lm): 81400

Lifting System: Manual lifting system

Maximum height (m): 5.5

Mast rotation: 350°

Lenght closed (mm): 1200 Width closed (mm): 841 Height closed (mm): 2200

With generator / Without generator: Without generator

Transportability: Wheels and handles Stability to wind (Km/h): 80 Km/h

Weight (Kg): 192



