

Ì

## ITALTOWER MT55 LIGHTING TOWER 4x75 W MULTILED

Product price:

## 1.669,00 € tax excluded

## **Product description:**

ITALTOWER MT55 LIGHTER TOWER 4x75 W MULTILED

ITALTOWER MT55 4x75W is a manually lifted lighting tower equipped with 4 floodlights capable of delivering a light output of 75W each.

ITALTOWER MT55 4x75 is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 5.5 meters. The tower is complete with a hand pump for raising and manual locking on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

ITALTOWER MT55 stands out for its performance, compactness and solidity, with its 4x75W LED, able to compete with much bulkier lighting towers equipped with a halogen system.

The ITALTOWER MT55 is suitable for a variety of large-scale construction work, maintenance repair, incident management and disaster relief work, high-brightness lighting needs.

The ITALTOWER MT55 4x75 is designed to be combined with a generator set and can be connected in series in order to use one generator for multiple lighting units.

The lightness of the ITALTOWER MT55 will also allow you to move it easily and thanks to the 4 feet, removable and foldable to optimize the space inside the container, you will be able to illuminate what you want.

ITALTOWER MT55 4x75 TECHNICAL FEATURES

Number of lights: 4 Lamps power: 75 W LED Lumen: 36900 lm Illuminated area: 1500 sqm

PrestaShop

R



Voltage: 230 V Frequency: 50 Hz Consumption: 4 X 75 W = 0. 3 KW Maximum height: 5.5m Lifting system: Manual Wind resistance: 80 Km/h Trolley: Stationary Stabilizers: 4 Length (mm): 640 Width (mm): 355 Height (mm): 1920 Dry weight (Kg): 95

Looking for a light tower with different technical characteristics? Here you can find the full range of lighting towers ITALTOWER or other brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## **Product features:**

Frequency (Hz): 50 Voltage (V): 230 Type of lamps: LED Lamps: 4 x 75 W Telescopic pole: Vertical Illuminated area (m<sup>2</sup>): 1500 Total lumens (Lm): 36900 Lifting System: Manual lifting system Maximum height (m): 5.5 Open size (mm): 2200 x 2200 x 5700 Lenght closed (mm): 355 Width closed (mm): 640 Height closed (mm): 1920 With generator / Without generator: Without generator Transportability: Stationary Stability to wind (Km/h): 80 Km/h Weight (Kg): 95