



ITALTOWER KT55 LIGHTING TOWER 4x160 W MULTILED

Product price:

1,827.00 € tax excluded

Product description:

ITALTOWER KT55 LIGHTER TOWER 4x160 W MULTILED

ITALTOWER KT55 4x160W is a manually lifted light tower equipped with 4 floodlights capable of delivering a light output of 160W each.

ITALTOWER KT55 4x160 is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 5.5 meters. The tower is equipped with a winch that allows the manual lifting of the telescopic pole in safety thanks to an iron cable made up of 133 anti-twisting micro-cables improving the resistance and the capacity of the winch itself.

The peculiarity of the tower is the fact that it is equipped with a winch that allows the manual lifting of the telescopic pole in safety thanks to an iron cable made up of 133 anti-twisting micro-cables improving the resistance and the capacity of the winch itself.

The particularity of the ITALTOWER KT55, are the 4 fixing holes at the base that allows it to be applied on generator sets or external supports and a rotation of the pole of 360°.

The ITALTOWER MT55 is suitable for a variety of large-scale construction work, maintenance repair, accident management and disaster relief work, high brightness lighting needs.

ITALTOWER KT55 4x160 is designed to be combined with a generator set and can be connected in series in order to use one generator for multiple lighting units.

ITALTOWER KT55 4x160 TECHNICAL FEATURES

Number of lights: 4
Lamps power: 160 W LED
Lumen: 81400 lm
Illuminated area: 2400 sqm



Voltage: 230 V
Frequency: 50 Hz
Consumption: 4x160W = 0.64 KW
Maximum height: 5. 5 m
Lifting system: Manual
Wind resistance: 80 Km/h
Trolley: Stationary
Stabilizers: Bolt-on base
Length (mm): 640
Width (mm): 350
Height (mm): 2089
Dry weight (Kg): 90

Looking for a light tower with different technical characteristics? [Here](#) you can find the full range of light towers ITALTOWER or other brands specializing in the sector.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Frequency (Hz): 50
Voltage (V): 230
Type of lamps: LED
Lamps: 4 x 160 W
Telescopic pole: Vertical
Illuminated area (m²): 2400
Total lumens (Lm): 81400
Lifting System: Manual lifting system
Maximum height (m): 5.5
Length closed (mm): 350
Width closed (mm): 640
Height closed (mm): 2089
With generator / Without generator: Without generator
Transportability: Stationary
Stability to wind (Km/h): 80 Km/h
Weight (Kg): 90

