



GENMAC GR2500iN SINGLE-PHASE 2.5 kW INVERTER GENERATOR

Product price:

820.00 € tax excluded

Product description:

GENMAC GR2500IN SINGLE-PHASE GENERATOR 2,5kW INVERTER

The Genmac GR2500iN single-phase generator is equipped with a 4-stroke R120-VI engine, powered by Gasoline, capable of delivering a maximum power of 2.5KW, super quiet thanks to the inverter provided.

The Genmac GR2500iN is particularly compact and lightweight, it can be carried by hand, easily to any place. The Genmac GR2500iN generator has an internal fuel tank with a capacity of 4.5 liters, guaranteeing an autonomy of about 3.0 hours. The small size and the sturdy handle located above the machine body, make it perfect for transport and easy placement during periods of inactivity.

All materials used for the manufacture of the Genmac GR2500iN, are of first choice, offering and guaranteeing the customer a tested and proven product at a very affordable price. Thanks to the electrical stabilizer of the Inverter technology that works at very low distortion, the generator delivers constant current loads without voltage spikes that could damage electrical and electronic devices.

Another advantage of the inverter is to work with variable engine speed, according to the need for current to be delivered, optimizing the best fuel consumption, gas emission and wear of mechanical parts. The Genmac GR2500iN is ideal for use in campsites, campers and for outdoor leisure time.

Thanks to the low noise impact obtained thanks to the inverter, it is possible to use the generator, even in environments where particularly loud noises can not be accepted, such as historic centers, hospitals, schools, gyms, etc.. Do not underestimate the considerable discomfort that you feel, to be all day near the noisy generators for work needs.

Technical characteristics Genmac GR2500iN:



Phase Type: Single Phase Nominal Power: 2.3 kW Maximum Power: 2.5 kW

Frequency: 50 Hz

Nominal Voltage: 230 V Voltage Regulator: Inverter Motor: R120-VI 4-stroke

RPM: 3000 rpm

Number of cylinders: 1 Displacement: 120 ml

Start: Manual Fuel: Gasoline

Fuel tank capacity: 4.5 L

Autonomy: 3.0 h

Noise level: 67 dBA @ 7m.

Length: 520 mm Width: 320 mm Height: 460 mm Weight: 23.5 Kg

Are you looking for a generator with different technical characteristics? <u>HERE</u> you can find the section dedicated to GENMAC generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase

Maximum power single phase (KW): 2.5 Continuous power single phase (KW): 2.3

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 Shucko + Thermal

Engine: 4 stroke

Engine rpm (rpm): 3000

Ignition: Recoil

Starting system: Manual Number cylinders: 1

Cooling: Air

Alternator: Synchronous Fuel tank capacity (L): 4.5

Running time (h): 3 at 75% of the load



Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 520 Width (mm): 320 Height (mm): 460 Dry weight (Kg): 23

Silenced: Yes

Super silenced: Yes ATS Switch device : No Voltage regulator: Inverter

