



# AURORA LIGHT TOWER ALPHA K-L 4X160 - S SLOW TOWING TROLLEY

**Product price:**

**9.572,16 € tax excluded**

## **Product description:**

AURORA LIGHTHOUSE TOWER ALPHA K-L 4X160 - S S SLOW TOWER

AURORA ALPHA K-L 4X160 - S is a light tower with diesel generator and manual hoisting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

AURORA ALPHA K-L 4X160 - S is equipped with a galvanized steel lifting system capable of extending up to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows the maximum extension without effort.

AURORA ALPHA K-L 4X160 - S is complete with Kohler KDW 702 engine, these engines are super efficient with 1500 rpm. THE TOWERS AURORA ALPHA K-L 4X160 - S in addition guarantee you an autonomy of 180 h of work at 30% of the load.

The AURORA light tower lenses feature extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA can cover an area of 3300 m<sup>2</sup>, ensuring a brighter, safer and more productive site.

AURORA ALPHA comes complete with a slow moving trolley, this gives the customer the ability to easily transport the light tower.

TECHNICAL FEATURES AURORA ALPHA K-L 4X160 - S

Manufacturer: Green Power



Projectors: 4 160W LEDs  
Lighted Area: 3300 Sq Ft  
Max Height: 8.5 Mt  
Rise: Manual  
Motor: Kohler KDW 702  
Emissions: Stage V  
Power supply: Diesel  
Engine speed: 1500 rpm  
Telescopic pole: Galvanized steel  
Max wind resistance: 100 Km/h  
Wind stability: nr 4 stabilizers  
Transport: Slow towing  
Noise level at 7 mt: 70 dB (A)  
Total lumens: 81400 lm  
Voltage: 230V  
Frequency: 50 Hz  
Autonomy 30% load: 180 hr  
Closed tower dimensions: 1154x1118x2430 mm  
Open tower dimensions: 2030x2202x8500 mm  
Dry weight: 560 Kg

Looking for a product with different characteristics? Here you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

#### **Product features:**

Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Starting system: Electric  
Type of lamps: LED  
Lamps: 4 x 160W  
Telescopic pole: Galvanized steel  
Illuminated area (m<sup>2</sup>): 3300  
Lifting System: Hydraulic lifting system  
Maximum height (m): 8.5  
Mast rotation: 359°  
Open size (mm): 2030x2202x8500 mm  
Closed size (mm): 1154x1118x2430 mm





Dry weight (Kg): 560

Engine manufacturer: Kohler KDW 702

Trailer type : traino lento

