



# MOSA GE 8000 KBT THREE-PHASE GENERATOR 8KVA STAGE V

**Product price:**

**1.220,00 € tax excluded**

## **Product description:**

MOSA GE 8000 KBT THREE-PHASE GENERATOR 8KVA STAGE V

MOSA GE8000 KBT is a single-phase/three-phase generator with KOHLER CH 440 Stage V powered by gasoline, capable of delivering a maximum power of 8 KVA.

MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 82 kg, equipped with practical tubular handles.

The MOSA GE8000 KBT is certified for Stage V European emission standards, this allows the handling of the generator.

The MOSA GE8000 KBT generator set is equipped with manual recoil start. The alternator of the MOSA GE8000 KBT generator set is synchronous, single-phase, self-excited, self-regulated, brushless and with class H insulation.

The control panel is equipped with a manual recoil starter.

The control panel is composed of:

- Output sockets: 1x400V 16A 3P+N +T CEE / 1x230V 16A 2P+T CEE
- Motor switch ON-OFF
- Air control
- Voltmeter
- Thermomagnetic circuit breaker
- Earth terminal (PE)

## **Technical specifications MOSA GE8000 KBT :**





Phase Type: SinglePhase/ThreePhase  
Maximum ThreePhase Output: 8 KVA  
Continuous ThreePhase Output: 7 KVA  
Maximum ThreePhase Output: 6.4 KW  
Continuous ThreePhase Output: 5.6 KW  
Continuous Single-phase Power: 4 KVA  
Continuous Single-phase Power: 3.2 KVA  
Fuel: Gasoline  
Voltage: 230 - 400 V  
Frequency: 50 Hz  
Motor: KOHLER CH 440 COMMAND PRO  
Emission Standard: Stage V  
Number of cylinders: 1  
Displacement: 429 cc  
Engine speed: 3000 rpm  
Tank capacity: 7 l  
Acoustic pressure: 74 dB(A) @ 7 m  
Alternator: Synchronous Brushless  
Length: 770 mm  
Width: 520 mm  
Height: 650 mm  
Weight: 82 Kg

If you are looking for another product like the MOSA GE8000 KBT generator set then you can check out our catalog for other land based generator sets.

Images and technical data are not binding.

#### Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 3.2  
Maximum power single phase (KVA): 4  
Maximum power three phase (KW): 6.4  
Continuous power three phase (KW): 5.6  
Maximum power three phase (KVA): 8  
Continuous power three phase (KVA): 7  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1x400V 16A 3P+N +T CEE / 1x230V 16A 2P+T CEE  
Engine: KOHLER CH440  
Emissions Regulations: Stage 5





Engine rpm (rpm): 3000  
Speed governor: Mechanical  
Ignition: Recoil  
Starting system: Pull starter  
Engine capacity (cm<sup>3</sup>): 429  
Number cylinders: 1  
Cooling: Air  
Alternator: Synchronous self-excited, self-regulated, brushless  
Bore x stroke (mm): 89 x69  
Compression ratio: 8.3 : 1  
Length (mm): 770  
Width (mm): 520  
Height (mm): 650  
Dry weight (Kg): 82  
Silenced: No  
ATS Switch device : No  
Voltage regulator: No  
Engine manufacturer: Kohler