




# CGM 80P-B100 WITH MANUAL CONTROL PANEL



Product price:

**14,227.50 € tax excluded**

## Product description:

### **CGM 80P-B100 Single/three-phase 80KVA generator with manual control panel**

The CGM 80P-B100 is a single/three phase 80KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 80P-B100 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 80P-B100 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 80P-B100 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 14 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 80P-B100 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

### **Technical characteristics of the CGM 80P-B100 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 70.4 KW / 88 KVA

Three-phase continuous power: 64 KW / 80 KVA

Maximum single-phase power: 23.47 KW / 29.33 KVA

Single-phase continuous use power: 21.33 KW / 26.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1104A-44TG2

Engine speed: 1500 rpm

Starting: Electric

Consumption: 14 Lt/h at 75% load

Length: 2100 mm

Width: 1000 mm



Height: 1800 mm  
Weight: 1010 Kg  
AVR

If you are looking for a product like the CGM 80P-B100 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 17.6  
Continuous power single phase (KW): 16  
Maximum power single phase (KVA): 29.3  
Continuous power single phase (KVA): 20  
Maximum power three phase (KW): 70.4  
Continuous power three phase (KW): 64  
Maximum power three phase (KVA): 88  
Continuous power three phase (KVA): 80  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Morsettiera  
Engine: Perkins 1104A-44TG2  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 4410  
Number cylinders: 4  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 105 x 127  
Fuel tank capacity (L): 120  
Consumption (L/h): 14  
Running time (h): 8.6  
Length (mm): 2100  
Width (mm): 1000  
Height (mm): 1800

---



Shop name

---

Dry weight (Kg): 1010

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins



PrestaShop