



## CGM 135P-C200 WITH AUTOMATIC CONTROL PANEL

**Product price:** 

23,085.00 € tax excluded

### **Product description:**

# CGM 135P-C200 Single/three-phase 135KVA generator super-silenced with automatic control panel

The CGM 135P-C200 is a single/three phase 135KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a sound-proofed cabin made of structural steel plate, weatherproofing and an interior lining made of sound-absorbing material with high noise reduction, which makes the CGM 135P-C200 supersilenced.

The CGM 135P-C200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 135P-C200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 22,7 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 135P-C200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

### Technical characteristics of the CGM 135P-C200 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 119.2 KW / 149 KVA Three-phase continuous power: 108 KW / 135 KVA Maximum single-phase power: 39.73 KW / 49.67 KVA Single-phase continuous use power: 36 KW / 45 KVA

Fuel: Diesel

Voltage: 230 V / 400 V Frequency: 50 Hz

Motor: PERKINS 1106A-70TG1

Engine speed: 1500 rpm



Starting: Electric

Consumption: 22.7 Lt/h at 75% load

Length: 3200 mm Width: 1100 mm Height: 2090 mm Weight: 1930 Kg Super-silenced

**AVR** 

If you are looking for a product like the CGM 135P-C200 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase

Maximum power single phase (KW): 39.73 Continuous power single phase (KW): 36 Maximum power single phase (KVA): 49.67 Continuous power single phase (KVA): 45 Maximum power three phase (KW): 119.2 Continuous power three phase (KWA): 108 Maximum power three phase (KVA): 149 Continuous power three phase (KVA): 135

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Morsettiera

**Engine: Yanmar L70N** 

**Emissions Regulations: Stationary Use** 

Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Elettrico Engine capacity (cm³): 7010

Number cylinders: 6 Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 105 x 135 Fuel tank capacity (L): 250



Consumption (L/h): 22.7 Running time (h): 11

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3200 Width (mm): 1100 Height (mm): 2090 Dry weight (Kg): 1930

Silenced: Yes

Super silenced: Yes
Product type: Generator
ATS Switch device: Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

