



# CGM 150P-B200 WITH AUTOMATIC CONTROL PANEL

**Product price:**

**24.613,00 € tax excluded**

## **Product description:**

CGM 150P-B200 Single/three-phase 150KVA generator with automatic control panel

The CGM 150P-B200 is a single/three phase 150KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 150P-B200 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 150P-B200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 150P-B200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 24,5 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 150P-B200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the CGM 150P-B200 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 132 KW / 165 KVA

Three-phase continuous power: 120 KW / 150 KVA

Maximum single-phase power: 44 KW / 55 KVA

Single-phase continuous use power: 40 KW / 50 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1106A-70TAG2

Engine speed: 1500 rpm

Starting: Electric

Consumption: 24.5 Lt/h at 75% load





Length: 2400 mm  
Width: 1100 mm  
Height: 2000 mm  
Weight: 1730 Kg  
AVR

If you are looking for a product like the CGM 150P-B200 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

### Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 44  
Continuous power single phase (KW): 40  
Maximum power single phase (KVA): 55  
Continuous power single phase (KVA): 50  
Maximum power three phase (KW): 132  
Continuous power three phase (KW): 120  
Maximum power three phase (KVA): 165  
Continuous power three phase (KVA): 150  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Perkins 1106A-70TAG2  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 7010  
Number cylinders: 6  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 105 x 135  
Fuel tank capacity (L): 250  
Consumption (L/h): 24.5  
Running time (h): 10.2  
Length (mm): 2400





Width (mm): 1100

Height (mm): 2000

Dry weight (Kg): 1730

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins