



CGM 200P-C200 WITH MANUAL CONTROL PANEL

Product price:

29,362.50 € tax excluded

Product description:

CGM 200P-C200 Single/three-phase 200KVA generator super-silenced with manual control panel

The CGM 200P-C200 is a single/three phase 200KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and lined with sound-absorbing material with high noise reduction, making the CGM 200P-C200 super-silenced.

The CGM 200P-C200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 200P-C200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 34,7 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 200P-C200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 200P-C200 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 176 KW / 220 KVA
Three-phase continuous power: 160 KW / 200 KVA
Maximum single-phase power: 58.67 KW / 73.33 KVA
Single-phase continuous use power: 53.33 KW / 66.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V Frequency: 50 Hz

Motor: PERKINS 1106A-70TAG4

Engine speed: 1500 rpm

Starting: Electric

Consumption: 34.7 Lt/h at 75% load



Length: 3200 mm Width: 1100 mm Height: 2090 mm Weight: 2150 Kg Super-silenced

AVR

If you are looking for a product like the CGM 200P-C200 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 58.67 Continuous power single phase (KW): 53.33 Maximum power single phase (KVA): 73.3 Continuous power single phase (KVA): 66.67 Maximum power three phase (KW): 176 Continuous power three phase (KW): 160 Maximum power three phase (KVA): 220 Continuous power three phase (KVA): 200

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Morsettiera Engine: Perkins 1106A-70TAG4

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm³): 7010

Number cylinders: 6 Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 105 x 135 Fuel tank capacity (L): 250 Consumption (L/h): 34.7 Running time (h): 15



Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3200 Width (mm): 1100 Height (mm): 2090 Dry weight (Kg): 2150

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: No Voltage regulator: AVR

Engine manufacturer: Perkins

