



# PRAMAC LIFTER GX 10/42 TRIPLEX EVO GEL ELECTRIC STACKER

Product price:

**10.103,00 € tax excluded**

## Product description:

### PRAMAC LIFTER GX 10/42 TRIPLEX EVO GEL ELECTRIC STACKER

PRAMAC LIFTER GX 10/42 TRIPLEX is a compact, powerful and robust forklift truck, ideal for working in confined spaces, thanks to the reduced width (800 mm), the side drawbar and wide uprights allow great maneuverability, stability and visibility.

PRAMAC LIFTER GX 10/42 can be used in a wide range of applications that require powerful lifting solutions: thanks to the three-stage telescopic mast, it is possible to stack goods even over **4 meters high**. It is equipped with maintenance-free GEL batteries that allow for a long service life and a large number of recharging cycles.

A specific electronic control allows stacker with proportional use. This PRAMAC LIFTER GX10/42 forklift truck is equipped with an integrated **Plug&Play charger** with cable and plug to facilitate the charging process and increase efficiency.

**The TRIPLEX mast** features three stacker stages capable of reaching considerable heights without compromising the operator's good visibility.

The combination of the three TRIPLEX stages with two side cylinders and a central cylinder allows free stacker without increasing the vertical footprint when the mast is closed, in order to work in containers or environments with low height.

The PRAMAC LIFTER GX10/42 stacker features an integrated ergonomic technopolymer tiller arm that includes as standard equipment the accelerator, proportional controls for the forks, safety button, horn, turtle button, display with hour meter and battery status indicator.

## TECHNICAL FEATURES PRAMAC LIFTER GX10/42 TRIPLEX

Propulsion Type: Electric





Driving System: Accompaniment  
Load capacity: 1000 Kg  
Rear wheels quantity: 2  
Front wheels quantity: 1 drive + 1  
Closed mast height: 1994 mm  
Free lift: 1370 mm  
Lifting height: 4110 mm  
Total length: 1800 mm  
Total width: 800 mm  
Fork width: 150 mm  
Fork length: 1150 mm  
Width between forks: 560 mm  
Storage corridor: 2240 mm  
Turning radius: 1430 mm  
Travel speed with load: 4.7 Km/h  
Travel speed without load: 5.2 Km/h  
Traction motor power: 0.7 KW

Are you looking for a product with different technical characteristics? Here you can find the area dedicated to the transport and storage of goods PRAMAC or other specialized brands, where you can find the product that suits you.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Drive: Electric  
Operator type: Pedestrian  
Load capacity (Kg): 1200  
Load centre distance (mm): 600  
Load axle to end forks (mm): 780  
Wheel base (mm): 1234  
Service weight (Kg): 618  
Axle load, laden rear (Kg): 1187  
Axle load, laden front (Kg): 631  
Axle load, unladen front (Kg): 456  
Axle load, unladen rear (Kg): 162  
Tyres: front wheels: RUBBER  
Tyres: stabilizers wheels: POLY.C.  
Tyres: rear wheels: POLY.C.  
Diameter steering wheels (mm): 250  
Width steering wheels (mm): 76  
Diameter load rollers (mm): 82





Width load rollers (mm): 70  
Diameter stabilizers wheels front (mm): 100  
Width stabilizers wheels front (mm): 38  
Quantity rear wheels: 2  
Quantity front wheels: 1 driven + 1  
Tread front (mm): 565  
Tread rear (mm): 410  
Height mast lowered (mm): 2250  
Normal free lifting (mm): 80  
Lift height (mm): 3410  
Height mast extended (mm): 3916  
Height of tiller in drive position max (mm): 1330  
Height of tiller in drive position min (mm): 960  
Height lowered (mm): 90  
Overall length (mm): 1760  
Length to face of forks (mm): 609  
Overall width (mm): 800  
Thickness fork (mm): 70  
Width fork (mm): 150  
Length fork (mm): 1150  
Fork carriage width (mm): 650  
Distance between fork arms (mm): 560  
Ground clearance at centre of wheelbase (mm): 20  
Aisle width (mm): 2210  
Turning radius (mm): 1430  
Travel speed laden (Km/h): 4.7  
Travel speed unladen (Km/h): 5.2  
Lifting speed laden (m/s): 0.11  
Lifting speed unladen (m/s): 0.19  
Lowering speed laden (m/s): 0.25  
Lowering speed unladen (m/s): 0.30  
Max gradeability laden (%): 5  
Max gradeability unladen (%): 10  
Service brake: Electric  
Drive motor power (KW): 0.7  
Lift motor power (KW): 2.2  
Battery voltage (V): 24  
Battery capacity min (Ah): 118  
Battery capacity max (Ah): 118  
Battery weight min (Kg): 34  
Battery weight max (Kg): 100  
Energy consumption according to VDI cycle (KWh/h): 0.9  
Sound level at driver's ear: 62  
Type of lifting: Electric

