



LUXTOWER LUX M11 PLUS LIGHT TOWER WITH FAST TOWING TROLLEY

Product price:

11.115,00 € tax excluded

Product description:

LUXTOWER LUX M11 PLUS LIGHT TOWER WITH FAST TOWING TROLLEY

LUXTOWER LUX M11 PLUS is a compact and easily transportable light tower that can effectively illuminate areas up to 4700 square meters, with a reduced environmental impact.

LUXTOWER LUX M11 PLUS light tower is equipped with a 9 meters vertical telescopic pole with manual lifting and 4x300 W LED floodlights with high luminous efficiency.

The lighting tower LUXTOWER LUX M11 PLUS is composed of a single-phase generating set of 3.5 KVA equipped with Kubota Z482 engine powered by diesel at 1500 rpm and soundproof enclosure that makes it supersilenced.

LUXTOWER LUX M11 PLUS is supplied complete with fast towing trolley complete with autonomous braking system, complete with rear lights with integrated reverse light and all the features for a proper urban and extra-urban transport.

OPTIONAL INCLUDED IN THE SUPPLY LUXTOWER LUX M11 PLUS

- DSE control system
- Generator network selector
- Twilight sensor
- Liquid collection tank

TECHNICAL FEATURES LUXTOWER LUX M11 PLUS

Projectors: 4 X 320W LED

Lighted Area: 4700 Sq Ft

Max Height: 9 Mt



Lift: Manual
Motor: Kubota Z482
Maximum Single-Phase Power: 3.5 KVA
Emissions Standard: STAGE V
Power Supply: Diesel
Engine RPM: 1500 rpm
Telescopic Pole: Galvanized Steel
Max Wind Resistance: 80 Km/h
Transportation: Road Trailer
Noise level at 7 mt: 65 dB (A)
Tank Capacity: 80 l
Runtime: 145 h
Consumption: 0. 55 l/h
Closed tower dimensions: 1800 X 1400 X 2600 mm
Open tower dimensions: 2400 X 2500 X 8000 mm
Dry weight: 700 Kg

If you are looking for more light towers like the LUXTOWER M11 then you can browse our entire catalog dedicated to beacon-towers of LUXTOWER or other brands.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KVA): 3.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: KUBOTA Z482
Engine rpm (rpm): 1500
Starting system: Electric
Number cylinders: 2
Cooling: Water
Alternator: Linz Alumen SP-E1C
Type of lamps: LED
Lamps: 4 x 320 W
Telescopic pole: Vertical
Illuminated area (m²): 4700
Lifting System: Manual lifting system
Maximum height (m): 9
Mast rotation: 340°
Open size (mm): 2400 X 2500 X 8000





Lenght closed (mm): 1800
Width closed (mm): 1400
Height closed (mm): 2600
With generator / Without generator: With generator
Transportability: Fast Trailer
Stability to wind (Km/h): 80 Km/h
Fuel tank capacity (L): 80
Consumption (L/h): 0.55
Running time (h): 145
Acoustic pressure: 65 dB(A) at 7 m
Dry weight (Kg): 700
Silenced: Yes
Super silenced: Yes
Product type: Light tower
Engine manufacturer: Kubota

