



CGM 500P-C500 WITH MANUAL CONTROL PANEL

Product price:

75,125.00 € tax excluded

Product description:

CGM 500P-C500 Single/three-phase 500KVA generator super-silenced with manual control panel

The CGM 500P-C500 is a single/three phase 500KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes the CGM 500P-C500 supersilenced.

The CGM 500P-C500 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 500P-C500 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 76 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 500P-C500 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 500P-C500 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 440 KW / 550 KVA
Three-phase continuous power: 400 KW / 500 KVA
Maximum single-phase power: 146.67 KW / 183.33 KVA
Single-phase continuous use power: 133.33 KW / 166.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 2506A-E15TAG2

Engine speed: 1500 rpm

Starting: Electric



Consumption: 76 Lt/h at 75% load

Length: 4850 mm Width: 1850 mm Height: 2550 mm Weight: 5140 Kg Super-silenced

AVR

If you are looking for a product like the CGM 500P-C500 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 146.67 Continuous power single phase (KW): 133.33 Maximum power single phase (KVA): 183.33 Continuous power single phase (KVA): 166.67

Maximum power three phase (KW): 440 Continuous power three phase (KW): 400 Maximum power three phase (KVA): 550 Continuous power three phase (KVA): 500

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Terminal box Engine: Perkins 2506A-E15TAG2

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 1520

Engine capacity (cm³): 15200

Number cylinders: 6 Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 137 x 171 Fuel tank capacity (L): 400 Consumption (L/h): 76



Running time (h): 5.3

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 4850 Width (mm): 1850 Height (mm): 2550 Dry weight (Kg): 5140

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: No Voltage regulator: AVR

Engine manufacturer: Perkins

