



CGM 30F-B50 WITH AUTOMATIC CONTROL PANEL

Product price:

8,857.50 € tax excluded

Product description:

CGM 30F-B50 Single/three-phase 30KVA generator with automatic control panel

The CGM 30F-B50 is a single/three phase 30KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This CGM 30F-B50 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 30F-B50 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 30F-B50 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 5,4 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 30F-B50 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 30F-B50 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 26.4 KW / 33 KVA

Three-phase continuous power: 24 KW / 30 KVA

Maximum single-phase power: 8.8 KW / 11 KVA

Single-phase continuous use power: 8 KW / 10 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT S8000 AM1

Engine speed: 1500 rpm

Starting: Electric

Consumption: 5.4 Lt/h at 75% load

Length: 1650 mm



Width: 850 mm
Height: 1600 mm
Weight: 690 Kg
AVR

If you are looking for a product like the CGM 30F-B50 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 8.8
Continuous power single phase (KW): 8
Maximum power single phase (KVA): 11
Continuous power single phase (KVA): 10
Maximum power three phase (KW): 26.4
Continuous power three phase (KW): 24
Maximum power three phase (KVA): 33
Continuous power three phase (KVA): 30
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Morsettiera
Engine: FPT (IVECO) S8000AM1
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³): 2900
Number cylinders: 3
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 104 x 115
Fuel tank capacity (L): 100
Consumption (L/h): 5.4
Running time (h): 18.5
Length (mm): 1650
Width (mm): 850



Height (mm): 1600

Dry weight (Kg): 690

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

