



CGM 150F-B200 WITH MANUAL CONTROL PANEL

Product price:

19,672.50 € tax excluded

Product description:

CGM 150F-B200 Single/three-phase 150KVA generator with manual control panel

The CGM 150F-B200 is a single/three phase 150KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This CGM 150F-B200 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 150F-B200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 150F-B200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 26 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 150F-B200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 150F-B200 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 132 KW / 165 KVA

Three-phase continuous power: 120 KW / 150 KVA

Maximum single-phase power: 44 KW / 55 KVA

Single-phase continuous use power: 40 KW / 50 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT NEF N67TM4

Engine speed: 1500 rpm

Starting: Electric

Consumption: 26 Lt/h at 75% load

Length: 2400 mm

Width: 1100 mm



Height: 2000 mm

Weight: 1620 Kg

AVR

If you are looking for a product like the CGM 150F-B200 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 44

Continuous power single phase (KW): 40

Maximum power single phase (KVA): 55

Continuous power single phase (KVA): 50

Maximum power three phase (KW): 132

Continuous power three phase (KW): 120

Maximum power three phase (KVA): 165

Continuous power three phase (KVA): 150

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: Morsettiera

Engine: FPT (IVECO) NEFN67TM4

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 6700

Number cylinders: 6

Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 104 x 132

Fuel tank capacity (L): 250

Consumption (L/h): 26

Running time (h): 9.6

Length (mm):

Width (mm): 1100

Height (mm): 360



Dry weight (Kg): 1620

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

