



GENSET MG 10001 SS-K SINGLE-PHASE GENERATOR 10KVA



Product price:

6,165.50 € tax excluded

Product description:

GENSET MG 10001 SS-K SINGLE-PHASE GENERATOR 10KVA

GENSET MG 10001 SS-K Singlephase generator with Kubota D722 StageV engine powered by diesel, capable of delivering a maximum power of 10KVA.

The GENSET MG 10001 SS-K is compact and easy to use, equipped with an enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 10001 SS-K is a single-phase 10KVA diesel generator set with electric start. This generator is also available with an automatic panel and remote control.

The GENSET MG 10001 SS-K generator, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The GENSET MG 10001 SS-K generator set includes:

- Automatic engine stop device with warning lights for:
 - battery charge failure
 - high water temperature
 - low fuel level
 - low oil pressure
- 12V built-in battery
- 1 singlephase EEC 230V - 32A
- 1 singlephase EEC 230V - 16A
- 1 singlephase Schuko 230V - 16A
- output protections
- Earth leakage circuit breaker
- Emergency stop button
- Fuel level indicator



- Hour meter
- Central lifting hook
- Arrangement for AMF-ATS or Remote control

TECHNICAL FEATURES GENSET MG 10001 SS-K

Phase Type: SinglePhase

Maximum SinglePhase Power: 10KVA / 8 KW

Continuous SinglePhase Power: 9 KVA / 7.2 KW

VAC Voltage: 230 V

Frequency (Hz): 50

Starting Frame: Electric

Motor: Kubota D722

Emission Standard: Stage V

RPM: 3000

Supply: Diesel

Fuel tank capacity: 30 l

Consumption @ 75 % load: 3.3 l/h

Autonomy @ 75 % load: 9.09 h

Acoustic pressure: 95 dB(A)

Length: 1360 mm

Width: 675 mm

Height: 860 mm

Net weight: 300 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 8

Continuous power single phase (KW): 7.2

Maximum power single phase (KVA): 10

Continuous power single phase (KVA): 9

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230



Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE - 1 x 230V 16A SCHUKO

Engine: Kubota D722

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 719

Number cylinders: 3

Cooling: Water

Alternator: Synchronous

Protection degree: IP23

Motor insulation class: H

Fuel tank capacity (L): 30

Consumption (L/h): 3.3

Running time (h): 9.09

Acoustic power: 95 dB(A)

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 1360

Width (mm): 674

Height (mm): 860

Dry weight (Kg): 300

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: No

Engine manufacturer: Kubota

