



CGM v18Y-C30 WITH MANUAL CONTROL PANEL

Product price:

9,875.00 € tax excluded

Product description:

CGM v18Y-C30 Single/three-phase 18KVA generator super-silenced with manual control panel

The CGM v18Y-C30 is a single/three phase 18KVA generator with a 1500 rpm Yanmar diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes the CGM v18Y-C30 supersilenced.

The CGM v18Y-C30 generator consists of a Linz, Stamford or Mecc Alte, self-excited, brushless alternator with AVR voltage regulator. The CGM v18Y-C30 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 4 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM v18Y-C30 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM v18Y-C30 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 15.8 KW / 19.8 KVA Three-phase continuous power: 14.4 KW / 18 KVA Maximum single-phase power: 5.27 KW / 6.6 KVA Single-phase continuous use power: 4.8 KW / 6 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: YANMAR 4TNV88-BIB

Engine speed: 1500 rpm

Starting: Electric



Consumption: 4 Lt/h at 75% load

Length: 1800 mm Width: 850 mm Height: 1275 mm Weight: 635 Kg Super-silenced

AVR

If you are looking for a product like the CGM v18Y-C30 then you can browse the full range of CGM <u>generators</u> or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 5.2
Continuous power single phase (KVA): 4.8
Maximum power single phase (KVA): 6.6
Continuous power single phase (KVA): 6
Maximum power three phase (KW): 15.8
Continuous power three phase (KVA): 19.8
Continuous power three phase (KVA): 19.8

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE

Engine: Yanmar 4TNV88-BIB Emissions Regulations: Stage 5

Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 2190

Number cylinders: 4 Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44
Bore x stroke (mm): 88 x 90
Fuel tank capacity (L): 100

Consumption (L/h): 4



Running time (h): 25

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1800 Width (mm): 850 Height (mm): 1275 Dry weight (Kg): 635

AVR: Yes Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: No Voltage regulator: AVR

Engine manufacturer: Yanmar

