



CGM e33Y-C30 WITH AUTOMATIC CONTROL PANEL

Product price:

9,727.50 € tax excluded

Product description:

CGM e33Y-C30 Single/three-phase 33KVA generator super-silenced with automatic control panel

The CGM e33Y-C30 is a single/three phase 33KVA generator with a 1500 rpm Yanmar diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and lined with soundproofing material with high noise reduction, which makes the CGM e33Y-C30 supersilenced.

The CGM e33Y-C30 generator consists of a Linz, Stamford or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM e33Y-C30 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 6,7 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM e33Y-C30 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM e33Y-C30 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 29 KW / 36.3 KVA

Three-phase continuous power: 26.4 KW / 33 KVA

Maximum single-phase power: 9.67 KW / 12.1 KVA

Single-phase continuous use power: 8.8 KW / 11 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: YANMAR 4TNV98-IGECS

Engine speed: 1500 rpm

Starting: Electric



Consumption: 6.7 Lt/h at 75% load

Length: 1800 mm

Width: 850 mm

Height: 1275 mm

Weight: 785 Kg

Super-silenced

AVR

If you are looking for a product like the CGM e33Y-C30 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 9.6

Continuous power single phase (KW): 8.8

Maximum power single phase (KVA): 12.1

Continuous power single phase (KVA): 11

Maximum power three phase (KW): 29

Continuous power three phase (KW): 26.4

Maximum power three phase (KVA): 36.3

Continuous power three phase (KVA): 33

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: Morsettiera

Engine: Yanmar 4TNV98-IGECS

Emissions Regulations: STAGE 3A

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 3319

Number cylinders: 4

Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 98 x 110

Fuel tank capacity (L): 100

Consumption (L/h): 6.7



Running time (h):

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1800

Width (mm): 850

Height (mm): 1275

Dry weight (Kg): 785

AVR: Yes

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Yanmar

