



CGM 330S-C300 WITH MANUAL CONTROL PANEL

Product price:

44,400.00 € tax excluded

Product description:

CGM 330S-C300 Single/three-phase 330KVA generator super-silenced with manual control panel

The CGM 330S-C300 is a single/three phase 330KVA generator with a 1500 rpm Scania diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining of soundproofing material with high noise reduction, which makes the CGM 330S-C300 super silenced.

The CGM 330S-C300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 330S-C300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 49 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 330S-C300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 330S-C300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 290.4 KW / 363 KVA

Three-phase continuous power: 264 KW / 330 KVA

Maximum single-phase power: 96.8 KW / 121 KVA

Single-phase continuous use power: 88 KW / 110 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: SCANIA DC09 072A 02 14

Engine speed: 1500 rpm

Starting: Electric



Consumption: 49 Lt/h at 75% load

Length: 3700 mm

Width: 1400 mm

Height: 2250 mm

Weight: 3430 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 330S-C300 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 96.8

Continuous power single phase (KW): 88

Maximum power single phase (KVA): 121

Continuous power single phase (KVA): 110

Maximum power three phase (KW): 290.4

Continuous power three phase (KW): 264

Maximum power three phase (KVA): 363

Continuous power three phase (KVA): 330

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: Morsettiera

Engine: Scania DC09 072A 02 14

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm³): 9300

Number cylinders:

Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 130 x 140

Fuel tank capacity (L): 250

Consumption (L/h): 49



Running time (h): 5.1

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3700

Width (mm): 1400

Height (mm):

Dry weight (Kg):

AVR: Yes

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Scania

