



CGM 410S-B400 WITH AUTOMATIC CONTROL PANEL

Product price:

43,072.50 € tax excluded

Product description:

CGM 410S-B400 Single/three-phase 410KVA generator with automatic control panel

The CGM 410S-B400 is a single/three phase 410KVA generator with a 1500 rpm Scania diesel engine, compact and easy to use, mounted on a fixed base. This CGM 410S-B400 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 410S-B400 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 410S-B400 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 60 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 410S-B400 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 410S-B400 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 360.8 KW / 451 KVA

Three-phase continuous power: 328 KW / 410 KVA

Maximum single-phase power: 120.27 KW / 150.33 KVA

Single-phase continuous use power: 109.33 KW / 136.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: SCANIA DC13 072A 02 12

Engine speed: 1500 rpm

Starting: Electric

Consumption: 60 Lt/h at 75% load



Length: 2950 mm
Width: 1550 mm
Height: 2100 mm
Weight: 3230 Kg
AVR

If you are looking for a product like the CGM 410S-B400 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 120.27
Continuous power single phase (KW): 109.33
Maximum power single phase (KVA): 150.33
Continuous power single phase (KVA): 136.67
Maximum power three phase (KW): 360.8
Continuous power three phase (KW): 328
Maximum power three phase (KVA): 451
Continuous power three phase (KVA): 410
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Morsettiera
Engine: Scania DC13 072A 02 12
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³): 12700
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 130 x 160
Fuel tank capacity (L): 400
Consumption (L/h): 60
Running time (h): 2,5
Width (mm): 1550



Height (mm): 2100

Dry weight (Kg): 3230

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Scania