



CGM 410S-C450 WITH AUTOMATIC CONTROL PANEL

Product price:

49.375,00 € tax excluded

Product description:

CGM 410S-C450 Single/three-phase 410KVA generator super-silenced with automatic control panel

The CGM 410S-C450 is a single/three phase 410KVA generator with a 1500 rpm Scania diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of sound-absorbing material with high noise reduction, which makes the CGM 410S-C450 supersilenced.

The CGM 410S-C450 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 410S-C450 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 60 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 410S-C450 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 410S-C450 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 360.8 KW / 451 KVA

Three-phase continuous power: 328 KW / 410 KVA

Maximum single-phase power: 120.27 KW / 150.33 KVA

Single-phase continuous use power: 109.33 KW / 136.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: SCANIA DC13 072A 02 12

Engine speed: 1500 rpm





Starting: Electric
Consumption: 60 Lt/h at 75% load
Length: 4300 mm
Width: 1750 mm
Height: 2350 mm
Weight: 4220 Kg
Super-silenced
AVR

If you are looking for a product like the CGM 410S-C450 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 120.27
Continuous power single phase (KW): 109.33
Maximum power single phase (KVA): 150.33
Continuous power single phase (KVA): 136.67
Maximum power three phase (KW): 360.8
Continuous power three phase (KW): 328
Maximum power three phase (KVA): 451
Continuous power three phase (KVA): 410
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: Scania DC13 072A 02 12
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 12700
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 130 x 160
Fuel tank capacity (L): 400





Consumption (L/h): 60
Running time (h): 6.7
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 4300
Width (mm): 1750
Height (mm): 2350
Dry weight (Kg): 4220
AVR: Yes
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Scania