



NANNI QMS12M60 SILENT MARINE GENERATOR 12KW 60 HZ EPA TIER III

Product description:

NANNI QMS12M60 SILENT MARINE GENERATOR 12KW 60 HZ EPA TIER III

NANNI QMS12M60 is a single phase marine generator equipped with a Kubota EPA Tier III, 4-stroke diesel engine capable of delivering a maximum power of 12KW at 60Hz.

The NANNI QMS12M60 is equipped with a Kubota EPA tier III certified base engine used for years in marine and industrial applications worldwide.

The NANNI QMS12M60 generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the NANNI QMS12M60 to operate at an optimal temperature. In the case of closed-loop heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The NANNI QMS12M60 is equipped with a closed-loop heat exchanger.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS12M60 is improved, resulting in low fuel consumption.

NANNI QMS12M60 is complete with fresh and salt water exchanger and anti-noise cabin making it super quiet.

TECHNICAL FEATURES NANNI QMS12M60

Phase Type: Single Phase

Maximum Power: 12 KVA / 12 KW

Continuous Use Power: 10.7 KVA / 10.7 KW



Fuel: Diesel
Voltage: 120 - 240 V
Frequency: 60 Hz
Engine: Kubota, 4-stroke
Emission Standard: EPA tier III
Engine Revs. 1800
Boosting: Electric
Consumption: 4 Lt/h at full load
Length: 1050 mm
Width: 540 mm
Height: 710 mm
Weight: 291 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range of NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase
Maximum power single phase (KW): 12
Continuous power single phase (KW): 10.7
Maximum power single phase (KVA): 12
Continuous power single phase (KVA): 10.7
Fuel: Diesel
Frequency (Hz): 60
Voltage (V): 120 / 240
Engine: Kubota, 4 stroke
Emissions Regulations: EPA tier III
Engine rpm (rpm): 1800
Starting system: Electric
Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Inyección : Indirect (E-TVCS)
Alternator: Electronic regulator
Consumption (L/h): 4 at 100% of the load
Length (mm): 1050
Width (mm): 540
Height (mm): 710
Dry weight (Kg): 291



Shop name

Silenced: Yes



PrestaShop