



CGM 150DS-C200 WITH AUTOMATIC CONTROL PANEL

Product price:

23,575.00 € tax excluded

Product description:

CGM 150DS-C200 Single/three-phase 150KVA generator super-silenced with automatic control panel

The CGM 150DS-C200 is a single/three phase 150KVA generator with a 1500 rpm Doosan diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and lined with sound-absorbing material with high noise reduction, making the CGM 150DS-C200 super-silenced.

The CGM 150DS-C200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 150DS-C200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 26 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 150DS-C200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 150DS-C200 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 136 KW / 170 KVA

Three-phase continuous power: 120 KW / 150 KVA

Maximum single-phase power: 45.33 KW / 56.67 KVA

Single-phase continuous use power: 40 KW / 50 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: DOOSAN DP086 TA

Engine speed: 1500 rpm

Starting: Electric



Consumption: 26 Lt/h at 75% load

Length: 3200 mm

Width: 1100 mm

Height: 2090 mm

Weight: 2230 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 150DS-C200 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 45.33

Continuous power single phase (KW): 40

Maximum power single phase (KVA): 56.6

Continuous power single phase (KVA): 50

Maximum power three phase (KW): 136

Continuous power three phase (KW): 120

Maximum power three phase (KVA): 170

Continuous power three phase (KVA): 150

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: Terminal box

Engine: DOOSAN DP086 TA

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm³): 8071

Number cylinders: 6

Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 111 x 139

Fuel tank capacity (L): 250

Consumption (L/h): 26



Running time (h): 9.6

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3200

Width (mm): 1100

Height (mm): 2090

Dry weight (Kg): 2230

AVR: Yes

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Doosan

