



CGM DUAL20000SP THREE-PHASE GENERATOR 20,7KVA AVR STAGE V

Product price:

3,202.50 € tax excluded

Product description:

CGM DUAL20000SP THREE-PHASE GENERATOR 20,7KVA AVR STAGE V

The CGM DUAL20000SP single-phase / three-phase Generator is equipped with OHV1000 Stage V gasoline engine, capable of delivering a power of 20,7KVA, complete with **Voltage regulator AVR**.

The CGM DUAL20000SP adapts perfectly to the most varied uses, thanks to the handling trolley that allows you to relocate it in perfect safety and simplicity. Thanks to the oversized 65-liter tank, this generator has an extraordinary autonomy of 6.6 hours at 75% load.

These CGM DUAL20000SP are equipped with high quality components, lightweight, compact, ease of use and also modern design, equipped with a practical electric start.

The alternator of CGM DUAL20000SP is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and AVR regulator.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the CGM DUAL20000SP to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for use at home, camping, hobby and leisure, but also for construction sites and craftsmen.

TECHNICAL FEATURES CGM DUAL20000SP

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Power: 20.7 KVA / 16.5 KW



Maximum ThreePhase Power: 20.7 KVA / 16.5KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Motor: OHV1000

Fuel: Gasoline

Motor RPM: 3000 rpm

Emission Standard: Stage V

Number of cylinders: 2

Displacement: 999 cc

Fuel tank capacity: 65 l

Consumption: 9.8 l @ 75%

Autonomy: 6.6 h

Alternator: Self-excited Brushless

Voltage regulator: AVR

Socket configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Width: 970 mm

Length: 680 mm

Height: 955 mm

Dry weight: 255 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the full range of CGM generators or other specialized brands

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 16.5

Maximum power single phase (KVA): 20,7

Maximum power three phase (KW): 16.5

Maximum power three phase (KVA): 20,7

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Engine: OHV1000

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Elettrico

Engine capacity (cm³): 999



Number cylinders: 2

Alternator: Self-excited Brushless

Fuel tank capacity (L): 65

Consumption (L/h): 9.8 l @ 75%

Running time (h): 6.6 at 75% of the load

Length (mm): 970

Width (mm): 680

Height (mm):

Dry weight (Kg):

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: CGM

