



CGM DUAL15000SP THREE-PHASE GENERATOR 15KVA AVR STAGE V

Product price:

2.055,00 € tax excluded

Product description:

CGM DUAL15000SP THREE-PHASE GENERATOR 15KVA AVR STAGE V

The CGM DUAL15000SP single-phase / three-phase Generator is equipped with OHV720 Stage V gasoline engine, capable of delivering a power of 15KVA, complete with **Voltage regulator AVR**.

The CGM DUAL15000SP adapts perfectly to the most varied uses, thanks to the handling trolley that allows you to relocate it in perfect safety and simplicity. Thanks to the oversized 40 liter tank, this generator has an extraordinary autonomy of 8,2 hours at 75% load.

These CGM DUAL15000SP are equipped with high quality components, lightweight, compact, ease of use and also modern design, equipped with a practical electric start.

The alternator of CGM DUAL15000SP is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and AVR regulator.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the CGM DUAL15000SP to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for use at home, camping, hobby and leisure, but also for construction sites and craftsmen.

TECHNICAL FEATURES CGM DUAL15000SP

Phase Type: Singlephase / Threephase

Singlephase Maximum Power: 13,8 KVA / 11 KW



Threephase Maximum Power: 15 KVA / 12 KW
Voltage: 230 / 400 V
Frequency: 50 Hz
Engine: OHV720
Fuel: Gasoline
Engine RPM: 3000 rpm
Emissions Standard: Stage V
Number of cylinders: 2
Displacement: 713 cc
Fuel tank capacity: 40 l
Fuel consumption: 4.9 l @ 75%
Range: 8.2 h
Alternator: Self-excited with brushes
Receptacle configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Voltage regulator: AVR
Width: 870 mm
Length: 588 mm
Height: 726 mm
Dry weight: 184 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of CGM generators or other specialized brands

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11
Maximum power single phase (KVA): 13.8
Maximum power three phase (KW): 12
Maximum power three phase (KVA): 15
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Engine: OHV720
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Elettrico
Engine capacity (cm³): 713
Number cylinders: 2
Alternator: Self-excited with brushes





Fuel tank capacity (L): 2
Consumption (L/h): 4.9 l @ 75%
Running time (h): 8.2 at 75% of the load
Length (mm): 870
Width (mm): 588
Height (mm): 726
Dry weight (Kg): 184
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: CGM