



CGM 400DS-B400 WITH MANUAL CONTROL PANEL

Product price:

45,450.00 € tax excluded

Product description:

CGM 400DS-B400 Single/three-phase 400KVA generator with manual control panel

The CGM 400DS-B400 is a single/three phase 400KVA generator with a 1500 rpm Doosan diesel engine, compact and easy to use, mounted on a fixed base. This CGM 400DS-B400 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 400DS-B400 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 400DS-B400 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 65 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 400DS-B400 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 400DS-B400 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 376 KW / 470 KVA
Three-phase continuous power: 320 KW / 400 KVA
Maximum single-phase power: 125.33 KW / 156.67 KVA
Single-phase continuous use power: 106.67 KW / 133.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V Frequency: 50 Hz

Motor: DOOSAN P158 LE Engine speed: 1500 rpm

Starting: Electric

Consumption: 65 Lt/h at 75% load

Length: 2950 mm Width: 1550 mm



Height: 2100 mm Weight: 3250 Kg

AVR

If you are looking for a product like the CGM 400DS-B400 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 125.33 Continuous power single phase (KW): 106.67 Maximum power single phase (KVA): 156.67 Continuous power single phase (KVA): 133.33

Maximum power three phase (KW): 376 Continuous power three phase (KW): 320 Maximum power three phase (KVA): 470 Continuous power three phase (KVA): 400

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Terminal box

Engine: DOOSAN P158 LE

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Electric Engine capacity (cm³): 14618

Number cylinders: 8

Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 128 x 142 Fuel tank capacity (L): 400 Consumption (L/h): 65 Running time (h): 6.1 Width (mm): 1550

Height (mm): 2100 Dry weight (Kg): 3250



AVR: Yes Silenced: No

Super silenced: No

Product type: Generator ATS Switch device: No Voltage regulator: AVR

Engine manufacturer: Doosan

