



CGM 500DS-B400 WITH AUTOMATIC CONTROL PANEL



Product price:

50.613,00 € tax excluded

Product description:

CGM 500DS-B400 Single/three-phase 500KVA generator with automatic control panel

The CGM 500DS-B400 is a single/three phase 500KVA generator with a 1500 rpm Doosan diesel engine, compact and easy to use, mounted on a fixed base. This CGM 500DS-B400 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 500DS-B400 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 500DS-B400 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 83 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 500DS-B400 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 500DS-B400 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 440 KW / 550 KVA

Three-phase continuous power: 400 KW / 500 KVA

Maximum single-phase power: 146.67 KW / 183.33 KVA

Single-phase continuous use power: 133.33 KW / 166.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: DOOSAN DP158 LD

Engine speed: 1500 rpm

Starting: Electric

Consumption: 83 Lt/h at 75% load

Length: 2950 mm





Width: 1550 mm
Height: 2100 mm
Weight: 3560 Kg
AVR

If you are looking for a product like the CGM 500DS-B400 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 146.67
Continuous power single phase (KW): 133.33
Maximum power single phase (KVA): 183.33
Continuous power single phase (KVA): 166.67
Maximum power three phase (KW): 440
Continuous power three phase (KW): 400
Maximum power three phase (KVA): 550
Continuous power three phase (KVA): 500
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: DOOSAN DP158 LD
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 14618
Number cylinders: 8
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 128 x 142
Fuel tank capacity (L): 400
Consumption (L/h): 83
Running time (h): 4.8
Width (mm): 1550
Height (mm): 2100



Dry weight (Kg): 3560

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Doosan