



CGM 230B-C300 WITH AUTOMATIC CONTROL PANEL

Product price:

27,540.00 € tax excluded

Product description:

CGM 230B-C300 Single/three-phase 230KVA generator super-silenced with automatic control panel

The CGM 230B-C300 is a single/three phase 230KVA generator with a 1500 rpm Baudouin diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining of soundproofing material with high noise reduction, which makes the CGM 230B-C300 super-silenced.

The CGM 230B-C300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 230B-C300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 38,1 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

The CGM 230B-C300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 230B-C300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 202 KW / 253 KVA

Three-phase continuous power: 184 KW / 230 KVA

Maximum single-phase power: 67.33 KW / 84.33 KVA

Single-phase continuous use power: 61.33 KW / 76.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: BAUDOUIN 6M16G250/5

Engine speed: 1500 rpm



Starting: Electric
Consumption: 38.1 Lt/h at 75% load
Length: 3700 mm
Width: 1400 mm
Height: 2250 mm
Weight: 2840 Kg
Super-silenced
AVR

If you are looking for a product like the CGM 230B-C300 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 67.33
Continuous power single phase (KW): 61.33
Maximum power single phase (KVA): 84.33
Continuous power single phase (KVA): 76.67
Maximum power three phase (KW): 202
Continuous power three phase (KW): 184
Maximum power three phase (KVA): 253
Continuous power three phase (KVA): 230
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Morsettiera
Engine: BAUDOUIN 6M16G250/5
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³):
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 126 x 130
Fuel tank capacity (L): 250



Consumption (L/h): 38.1
Running time (h): 6.6
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 3700
Width (mm): 1400
Height (mm):
Dry weight (Kg): 2840
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: BAUDOUIN