



CGM 350B-B400 WITH MANUAL CONTROL PANEL

Product price:

36,120.00 € tax excluded

Product description:

CGM 350B-B400 Single/three-phase 350KVA generator with manual control panel

The CGM 350B-B400 is a single/three phase 350KVA generator with a 1500 rpm Baudouin diesel engine, compact and easy to use, mounted on a fixed base. This CGM 350B-B400 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 350B-B400 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 350B-B400 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 60,6 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 350B-B400 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 350B-B400 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 308 KW / 385 KVA
Three-phase continuous power: 280 KW / 350 KVA
Maximum single-phase power: 102.67 KW / 128.33 KVA
Single-phase continuous use power: 93.33 KW / 116.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: BAUDOUIN 6M21G385/5

Engine speed: 1500 rpm

Starting: Electric

Consumption: 60.6 Lt/h at 75% load

Length: 2950 mm Width: 1550 mm



Height: 2100 mm Weight: 3245 Kg

AVR

If you are looking for a product like the CGM 350B-B400 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 102.67 Continuous power single phase (KW): 93.33 Maximum power single phase (KVA): 128.3 Continuous power single phase (KVA): 116.67

Maximum power three phase (KW): 308
Continuous power three phase (KW): 280

Maximum power three phase (KVA):

Continuous power three phase (KVA): 350

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Morsettiera Engine: BAUDOUIN 6M21G385/5

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm³): Number cylinders: 6

Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 127 x 165 Fuel tank capacity (L): 400 Consumption (L/h): 60.6 Running time (h): 6.6 Width (mm): 1550 Height (mm): 2100

Dry weight (Kg): 3245



Silenced: No

Super silenced: No Product type: Generator ATS Switch device : No Voltage regulator: AVR
Engine manufacturer: BAUDOUIN

