



GENERATING SET 100KVA WITH MANUAL CONTROL PANEL

Product price:

17.763,00 € tax excluded

Product description:

Single/three-phase 100KVA generator super-silenced with manual control pane

Technical characteristics of the generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 88 KW / 110 KVA

Three-phase continuous power: 80 KW / 100 KVA

Maximum single-phase power: 29.33 KW / 36.67 KVA

Single-phase continuous use power: 26.67 KW / 33.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT NEF N45TM2A

Engine speed: 1500 rpm

Starting: Electric

Consumption: 15.5 Lt/h at 75% load

Length: 2300 mm

Width: 1050 mm

Height: 1590 mm

Weight: 1410 Kg

Super-silenced

AVR

Images and technical data are not binding.

Product features:





Phase: Single phase / Three phase
Maximum power single phase (KW): 29.33
Continuous power single phase (KW): 26.67
Maximum power single phase (KVA): 36.6
Continuous power single phase (KVA): 33.33
Maximum power three phase (KW): 88
Continuous power three phase (KW): 80
Maximum power three phase (KVA): 110
Continuous power three phase (KVA): 100
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: FPT (IVECO) NEFN45TM2A
Emissions Regulations: Stage 2
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 4500
Number cylinders: 4
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 104 x 132
Fuel tank capacity (L): 120
Consumption (L/h): 15.5
Running time (h): 7.7
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 2300
Width (mm): 1050
Height (mm): 1590
Dry weight (Kg): 1410
AVR: Yes
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: FPT Iveco

