



CGM v20KH-B20 WITH MANUAL CONTROL PANEL

Product price:

8.738,00 € tax excluded

Product description:

CGM v20KH-B20 Single/three-phase 20KVA generator with manual control panel

The CGM v20KH-B20 is a single/three phase 20KVA generator with a 1500 rpm Kohler diesel engine, compact and easy to use, mounted on a fixed base. This CGM v20KH-B20 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM v20KH-B20 generator consists of a Linz, Stamford or Mecc Alte, self-excited, brushless alternator with AVR voltage regulator. The CGM v20KH-B20 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 3,4 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM v20KH-B20 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM v20KH-B20 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 17.6 KW / 22 KVA

Three-phase continuous power: 16 KW / 20 KVA

Maximum single-phase power: 5.87 KW / 7.33 KVA

Single-phase continuous use power: 5.33 KW / 6.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: KOHLER KDI 1903M

Engine speed: 1500 rpm

Starting: Electric

Consumption: 3.4 Lt/h at 75% load

Length: 1400 mm

Width: 700 mm



Height: 1400 mm
Weight: 485 Kg
AVR

If you are looking for a product like the CGM v20KH-B20 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 5.8
Continuous power single phase (KW): 5.33
Maximum power single phase (KVA): 7.3
Continuous power single phase (KVA): 6.67
Maximum power three phase (KW): 17.6
Continuous power three phase (KW): 16
Maximum power three phase (KVA): 22
Continuous power three phase (KVA): 20
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE
Engine: Kohler KDI 1903 M
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 1861
Number cylinders: 3
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 88 x 102
Fuel tank capacity (L): 55
Consumption (L/h): 3.4
Running time (h): 16.2
Length (mm): 1400
Width (mm): 700
Height (mm): 1400



Dry weight (Kg): 485

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Kohler