



BM2 DR 35 PROFESSIONAL DEHUMIDIFIER 351/24h

Product price:

1.458,00 € tax excluded

Product description:

BM2 DR35 PROFESSIONAL DEHUMIDIFIER 35I/24h

BM2 DR35 is a professional dehumidifier, autonomous, operating without the need for installation, simply by connecting a plug to the mains, capable of dehumidifying up to 35 I every 24 hours.

BM2 DR35 you have the ability to enter the desired humidity value via the handy digital display. The rest is regulated by the dehumidifier in a completely automatic way.

During operation you can see on the display of the BM2 DR35 the precise values of humidity and temperature in the room, as well as a diagnostic page where you can analyze the malfunctions and parameters of the refrigerant circuit.

The new and modern electronic control, together with the electronic humidistat as standard, optimizes the use of the dehumidifier making it work only when needed. The control panel of the BM2 DR35 is placed in a convenient location and easily accessible by the user, who can set the desired degree of humidity using the "soft touch" buttons.

The BM2 DR35 control panel is placed in a convenient location and easily accessible by the user, who can set the desired degree of humidity using the "soft touch" buttons.

The BM2 DR35 allows to dehumidify large working areas, such as warehouses, cellars, always maintaining the humidity level set by the user.

As standard, the electronic control manages two hour meters, one resettable and one cumulative: indispensable and practical for rental, several accessory pages and a diagnostic page where malfunctions and parameters of the refrigeration circuit





can be analysed. BM2 DR35

TECHNICAL FEATURES BM2 DR35:

Phase type: Single-phase

Frequency: 50Hz

Dehumidification capacity: 35 I/24h

Airflow rate: 290 m3/h Tank capacity: 7 l

Operating temperature: 3 - 40 °C Operating humidity: 20 - 100 %

Compressor type: rotary

Electrical power input: 0. 609W

Refrigerant: R407C Protection class: IPX4

Pressure acoustics: 56 dBA @ 1 m

Dehumidifying capacity (@ 32°C - 90%): 35.18 l/24h Dehumidifying capacity (@ 30°C - 80%): 29.88 l/24h Dehumidifying capacity (@ 15°C - 70%): 14.04 l/24h

Specific energy consumption(@ 32°C - 90%): 0.42 kWh/liter Specific energy consumption(@ 30°C - 80%): 0.46 kWh/liter Specific energy consumption(@ 15°C - 70%): 0.71 kWh/liter

Width: 496 mm Depth: 470 mm Height: 724 mm Net weight: 40 Kg

BM2 DR35

Are you looking for a dehumidifier with different characteristics? Here you can find the full range BM2 or other brands specializing in the field

The images are purely indicative.

Product features:

Phase: Single phase Frequency (Hz): 50 Voltage (V): 230

Protection degree: IPX4

Air flow (m³/h): 290

Acoustic pressure: 56 dBA @ 1 m

Length (mm): 496





Width (mm): 470 Height (mm): 724 Dry weight (Kg): 40

Container capacity (L): 7 Power consumption (W): 609

Coolant: R407C

Specific energy consumption (@ 32°C - 90%) kWh/liter: 0.42 Specific energy consumption(@ 30°C - 80%) kWh/liter: 0.46 Specific energy consumption(@ 15°C - 70%) kWh/liter: 0.71

Dehumidification capacity (@ 32°C - 90%) I/24h: 35.18 Dehumidification capacity (@ 30°C - 80%) I/24h: 29.88 Dehumidification capacity (@ 15°C - 70%) I/24h: 14.04

