



Shop name



MOSA TS 500 PS BC MMA Arc Gouging Welder with Polarity Change

Product price:

13,566.94 € tax excluded

Product description:

The engine-driven welder TS 500 PS BC 60Hz is a professional machine with electronic control of the welding current capable of delivering up to 500 A with a duty cycle of 60%.

Equipped with a Perkins water cooled diesel engine 400 series and an asynchronous alternator and thanks to the lower engine speed (1500 rpm) it is suitable for continuous operation in all conditions and can be used simultaneously as a welder and as a three-phase and single-phase electrical generator up to 20 kVA.

The TS 500 PS-BC 60Hz is designed to satisfy the requirements of professional welding with direct current and can weld any kind of electrode (rutile, basic, cellulose) up to 8 mm in diameter. The characteristic BC (base current) is particularly suitable for vertical down pipe welding.

It is a super-silenced engine-driven welder with compact canopy. It can function simultaneously as a welder and as a three-phase and single-phase electrical generator.

Suitable for a wide range of applications, including large metal fabrications oil pipelines and construction sites.

In accordance with CE regulation

WELDING

Current range, continuous: 20 ÷ 500A

Duty cycle: 500A-35%; 450A-60%; 400A-100%

Open circuit voltage: 70 V

Arc welding source in D.C. welding

Electronic regulation of welding current

Welds any type of electrode, including cellulosic

Special BC (Base Current) circuit for vertical-down pipe welding

Double welding output (20A-200A / 20A-400A)

Arc Gouging dedicated socket

A.C. generator, single-phase and three-phase

Aux power also available while welding

GENERAL

Dry weight: 780 kg



Dimensions: 1720x980x1110 mm

Acoustic power LwA (pressure LpA) : 94 dB(A) (69 dB(A) @ 7m)

VERSIONS ON REQUEST

Auxiliary output 400Y - 230I - 48I : 1x400V 32A 3P+N+T CEE - 1x230V 32A 2P+T CEE - 1x230V 16A 2P+T CEE

Auxiliary output 400Y - 230I - 110I : 1x400V 32A 3P+N+T CEE - 1x230V 32A 2P+T CEE - 1x110V 32A 2P+T CEE - 1x110V 16A 2P+T CEE

TS 500 PS-PL: Version with polarity change

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 9.6

Maximum power single phase (KVA): 12

Maximum power three phase (KW): 12.8

Maximum power three phase (KVA): 16

Fuel: Diesel

Frequency (Hz): 60

Voltage (V): 230 / 400

Engine: PERKINS 404D-22G, 4 stroke, naturally aspirated

Engine rpm (rpm): 1800

Starting system: Electric

Engine capacity (cm³): 2216

Number cylinders: 4

Cooling: Water

Inyección : Indirect

Alternator: Asynchronous three-phase, self-excited, self-regulated, brushless

Regulation current (A): 20 - 500

Welding current (A): 500 at 35% - 450 at 60% - 400 at 100%

Open circuit voltage (V): 70

Maximum diameter electrodes (mm): 8

Type of welding current: DC

Type of welding: MMA

Fuel tank capacity (L): 60

Consumption (L/h): 4.2

Running time (h): 14.5

Acoustic power: 94 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1720

Width (mm): 980

Height (mm): 1110

Dry weight (Kg): 780

Silenced: Yes



Shop name

Super silenced: Yes

Engine manufacturer: Perkins



PrestaShop