



# CGM e25KH-B20 WITH AUTOMATIC CONTROL PANEL

**Product price:**

**9.325,00 € tax excluded**

## **Product description:**

CGM e25KH-B20 Single/three-phase 25KVA generator with automatic control panel

The CGM e25KH-B20 is a single/three phase 25KVA generator with a 1500 rpm Kohler diesel engine, compact and easy to use, mounted on a fixed base. This CGM e25KH-B20 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM e25KH-B20 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM e25KH-B20 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 4,4 litres per hour at 75% load. It also has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM e25KH-B20 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the CGM e25KH-B20 generator:**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 22 KW / 27.5 KVA

Three-phase continuous power: 20 KW / 25 KVA

Maximum single-phase power: 7.33 KW / 9.17 KVA

Single-phase continuous use power: 6.67 KW / 8.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: KOHLER KDI 2504M

Engine speed: 1500 rpm

Starting: Electric

Consumption: 4.4 Lt/h at 75% load

Length: 1400 mm



Width: 700 mm  
Height: 1400 mm  
Weight: 530 Kg  
AVR

If you are looking for a product like the CGM e25KH-B20 then you can browse the full range of CGM generators or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

### Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 7.33  
Continuous power single phase (KW): 6.67  
Maximum power single phase (KVA): 9.1  
Continuous power single phase (KVA): 8.3  
Maximum power three phase (KW): 22  
Continuous power three phase (KW): 20  
Maximum power three phase (KVA): 27.5  
Continuous power three phase (KVA): 25  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Kohler KDI 2504 M  
Emissions Regulations: Stage 3A  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2482  
Number cylinders: 4  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 88 x 102  
Fuel tank capacity (L): 55  
Consumption (L/h): 4.4  
Running time (h): 12.5  
Length (mm): 1400  
Width (mm): 700





Height (mm): 1400

Dry weight (Kg): 530

AVR: Yes

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Kohler