



# GREEN POWER GP 6000XM/KM SINGLE PHASE GENERATOR STAGE V MANUAL START 5,5KVA

Product price:

**790,60 € tax excluded**

## Product description:

GREEN POWER GP 6000XM/KM SINGLE PHASE GENERATOR STAGE V MANUAL START 5,5KVA

The Generator GREEN POWER GP 6000XM/KM single-phase is equipped with a KOHLER CH 395 **StageV** engine supplied by gasoline, and comes complete with capacitor voltage regulator (**AVR optional**).

GREEN POWER GP 6000XM/KM is equipped with manual recoil start with self-winding and has a low fuel consumption, in fact it consumes only 1,8 liter/hour at 75% load for a range of up to 3.9 hours of operation. Extremely practical sockets and controls facilitate the start-up and operation of the generator making these operations extremely simple and fast.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 68 kg as well as the practical tubular handles.

The generator features an engine support system with a durable steel frame and rubber shock absorbers.

## STAGEV EMISSION STANDARDS

The STAGEV standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.



---

## TECHNICAL FEATURES GREEN POWER GP 6000XM/KM

Phase type: Single-phase  
Continuous duty: 5 KVA / 5 KW  
Maximum power: 5.5 KVA / 5.5 KW  
Motor: KOHLER CH 395  
Engine speed: 3000 rpm  
Emission regulation: StageV  
Starting: Manual recoil  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 16A 230V  
Tank capacity: 7 l  
Autonomy at 75% load: 3.9 h  
Consumption at 75% load: 1,8 Lt/h  
Length: 700 mm  
Width: 570 mm  
Height: 630 mm  
Dry weight: 68 Kg

Are you looking for a generator with different technical characteristics? HERE you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

### Product features:

Phase: Single phase  
Maximum power single phase (KW): 5.5  
Continuous power single phase (KW): 5  
Maximum power single phase (KVA): 5.5  
Continuous power single phase (KVA): 5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x Schuko 16A 230V / 1 x CEE 16A 230V  
Engine: Kohler CH 395, 4 stroke  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Pull starter with recoil  
Engine capacity (cm³): 277  
Number cylinders: 1





---

Cooling: Air  
Alternator: LINZ SP10 MG  
Poles: 2  
Fuel tank capacity (L): 7  
Consumption (L/h): 1.8 at 75% of the load  
Running time (h): 3.9 at 75% load  
Length (mm): 570  
Width (mm): 700  
Height (mm): 630  
Dry weight (Kg): 68  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Kohler

