



GREEN POWER GP 6000XM/KE SINGLE- PHASE GENERATOR STAGE V ELECTRIC START 5,5KVA

Product price:

1.038,00 € tax excluded

Product description:

GREEN POWER GP 6000XM/KE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 5,5KVA

The generator GREENPOWER GP 6000XM/KE single-phase generator is equipped with a KOHLER CH 395 **StageV** gasoline-supplied engine, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/KE is equipped with electric start and has a low fuel consumption, in fact it consumes only 1.8 liters/hour at 75% load for a range of up to 3.9 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 79 kg as well as the practical tubular handles. In addition it is equipped with a practical and convenient electric start system, so it can be put into operation quickly and easily.

The GREENPOWER GP 6000XM/KE generator is equipped with a high performance KOHLER CH 395 StageV engine that allows this machine to deliver a maximum single-phase power of 5.5KVA.

VOLTAGE REGULATOR

The voltage regulator is an electronic device able to automatically regulate the voltage and eventually the frequency and/or the electric current according to set values. These values can be modified or bound to the technical characteristics of the regulator itself.





In essence, thanks to this device, the alternating current coming from the alternator is regulated and transformed into direct current at constant voltage.

The front panel of the GREENPOWER GP 6000XM/KE generator consists of:

- Thermal circuit breaker;
- 1 Schuko socket 16A 230V
- 1 CEE socket 16A 230V

TECHNICAL FEATURES GREENPOWER GP 6000XM/KE

Phase Type: Single Phase
Continuous Use Power: 5 KVA / 5 KW
Maximum Power: 5.5 KVA / 5.5 KW
Motor: KOHLER CH 395
Motor RPM: 3000 rpm
Emissions Standard: Stage V
Start: Electric
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 16A 230V
Tank capacity: 7 l
Run time at 75% load: 3.9 h
Consumption at 75% load: 1.8 Lt/h
Length: 780 mm
Width: 570 mm
Height: 680 mm
Dry weight: 79 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 5.5
Continuous power single phase (KW): 5
Maximum power single phase (KVA): 5.5
Continuous power single phase (KVA): 5
Fuel: Gasoline





Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x Schuko 16A 230V / 1 x CEE 16A 230V
Engine: Kohler CH 395, 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Elettrico
Engine capacity (cm³): 277
Number cylinders: 1
Cooling: Air
Alternator: LINZ SP10 MG
Poles: 2
Fuel tank capacity (L): 7
Consumption (L/h): 1.8 at 75% of the load
Running time (h): 3.9 at 75% load
Length (mm): 570
Width (mm): 780
Height (mm): 680
Dry weight (Kg): 79
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Kohler