



GREEN POWER GP 12000XT/HE GENERATOR SINGLE-PHASE/THREE-PHASE STAGE V ELECTRIC START 11KVA

Product price:

3,038.00 € tax excluded

Product description:

GREEN POWER GP 12000XT/HE GENERATOR SINGLE / THREE-PHASE STAGE V 11KVA

The generator GREENPOWER GP 12000XT/HE single / three-phase, is equipped with a HONDA GX630 **StageV** gasoline-supplied engine, and is complete with Compound voltage regulator (**AVR optional**).

GREENPOWER GP 12000XT/HE features a large 20-liter fuel tank and low fuel consumption, only 3.8 liters/hour at 75% load for up to 5.3 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The alternator of the StageV generator is the model MECC ALTE T20FS-130/A (or equivalent primary brand) and is synchronous, three-phase, with brushes and with class H insulation, in addition it is equipped with a voltage regulator. The generator is ducted with a practical electric start system.

One of the main features of the GREENPOWER GP 12000XT/HE is the motor/alternator coupling in single bearing by means of a cone, on an electro-welded steel base with the interposition of anti-vibration mounts.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 175 kg as well as the practical tubular handles. In addition, it is equipped with a practical and convenient electric starting system.

The GREENPOWER GP 12000XT/HE generator is equipped with HONDA GX630 StageV engine



that allows this machine to deliver a maximum three-phase power of 11KVA.

STAGEV EMISSION STANDARDS

The STAGEV standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to function correctly is that the genset works at its design temperature.

The electric control panel of the GREENPOWER GP 12000XT/HE is composed of:

- Sockets: 1 x CEE 16A 400V / 1 x CEE 16A 230V

- Starting key

- Voltmeter

- Low oil pressure led

- Circuit breaker + differential

TECHNICAL FEATURES GREENPOWER GP 12000XT/HE

Phase Type: SinglePhase/ThreePhase

Continuous Use SinglePhase Power: 3.4 KVA / 2.7 KW

Maximum SinglePhase Power: 3.7 KVA / 3 KW Continuous Use ThreePhase Power: 10 KVA / 8 KW

Maximum ThreePhase Power: 11 KVA / 8.8 KW

Motor: HONDA GX630 Motor RPM: 3000 rpm

Emission Standard: StageV

Start: Electric Fuel: Gasoline

Voltage: 230 / 400 V Frequency: 50 Hz

Socket panel: 1 x CEE 16A 230V / 1 x CEE 16A 400V

Tank capacity: 20 I

Run time at 75% load: 5.3 h

Consumption at 75% load: 3.8 Lt/h

Length: 780 mm Width: 570 mm Height: 780 mm Dry weight: 175 Kg

Are you looking for a generator with different technical features? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.



Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 3
Continuous power single phase (KW): 2.7
Maximum power single phase (KVA): 3.7
Continuous power single phase (KVA): 3.4
Maximum power three phase (KW): 8.8
Continuous power three phase (KW): 8
Maximum power three phase (KVA): 11
Continuous power three phase (KVA): 10

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE

Engine: Honda GX630, 4 stroke Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Elettrico Engine capacity (cm³): 688

Number cylinders: 2

Cooling: Air

Alternator: MECC ALTE T20FS-130/A

Poles: 2

Fuel tank capacity (L): 20

Consumption (L/h): 3.8 At 75 % Of Load Running time (h): 5.3 at 75% of the load

Length (mm): 780 Width (mm): 570 Height (mm): 780 Dry weight (Kg): 175

Silenced: No

Super silenced: No

Product type: Generator ATS Switch device: No

Voltage regulator: Compound / AVR (optional)

Engine manufacturer: Honda

